

Waste Tank Summary Report for Month Ending April 30, 1997



Prepared for the U.S. Department of Energy Assistant Secretary for Environmental Management

Project Hanford Management Contractor for the U.S. Department of Energy under Contract DE-AC06-96RL13200

Approved for public release; distribution is unlimited

Waste Tank Summary Report for Month Ending April 30, 1997

B. M. Hanlon Lockheed Martin Hanford Corp.

Date Published June 1997

Prepared for the U.S. Department of Energy Assistant Secretary for Environmental Management

Project Hanford Management Contractor for the U.S. Department of Energy under Contract DE-AC06-96RL13200

Approved for public release; distribution is unlimited

APPROVALS

Prepared by:

B. M. Hanlon

Responsible Manager:

G. L. Dunford, Manager West Tank Farms Engineering

WASTE TANK SUMMARY REPORT

B. M. Hanlon

ABSTRACT

This report is the official inventory for radioactive waste stored in underground tanks in the 200 Areas at the Hanford Site. Data that depict the status of stored radioactive waste and tank vessel integrity are contained within the report. This report provides data on each of the existing 177 large underground waste storage tanks and 63 smaller miscellaneous underground storage tanks and special surveillance facilities, and supplemental information regarding tank surveillance anomalies and ongoing investigations. This report is intended to meet the requirement of U. S. Department of Energy-Richland Operations Office Order 5820.2A, Chapter I, Section 3.e. (3) (DOE-RL, 1990, Radioactive Waste Management, U. S. Department of Energy-Richland Operation Office, Richland, Washington) requiring the reporting of waste inventories and space utilization for Hanford Tank Farm Tanks.

CONTENTS

		ige
SU	MMARY	
I.	WASTE TANK STATUS	ĺ
II.	WASTE TANK INVESTIGATIONS	
Ш	SURVEILLANCE AND WASTE TANK STATUS HIGHLIGHTS	2
Αţ	pendixes:	
A.	WASTE TANK SURVEILLANCE MONITORING TABLES A	\ -1
	1 Watch List Tanks A-2	
	2 Additions/Deletions to Watch List Tanks by Year	
	3 Temperature Monitoring in Watch List Tanks	
	4 Temperature Monitoring in Non-Watch List Tanks	
	5 Single-Shell Tanks Monitoring Compliance Status	
	6 Double-Shell Tanks Monitoring Compliance Status	
	8 Tank Monitor and Control System (TMACS) Monitoring Status	
	Control of the contro	
В.	DOUBLE-SHELL TANK WASTE TYPE AND SPACE ALLOCATION	3-1
	1 Double-Shell Tank Waste Type and Space Allocation B-2	
	2 Double-Shell Tank Waste Inventory	
	Figures:	
	1 Total Double-Shell Tank Total Inventory B-5	
C.	TANK AND EQUIPMENT CODE AND STATUS DEFINITIONS	C-1
_	1 Tank and Equipment Code/Status Definitions	/ - 1
D.	TANK FARM CONFIGURATION, STATUS AND FACILITY CHARTS) -1
	1 High-Level Waste Tank Configuration	
	2 Double-Shell Tank Instrumentation Configuration	
	3 Single-Shell Tank Instrumentation Configuration D-4	
E.	MONTHLY SUMMARY E	3-1
	1 Monthly Summary E-2	
	2 Tank Use Summary	
	3 Pumping Record, and Liquid Status and Pumpable Liquid Remaining	
	In Tanks E-4 4 Inventory Summary by Tank Farm E-5	
	5 Inventory and Status by Tank - Double-Shell Tanks	
	6 Inventory and Status by Tank - Single-Shell Tanks	
F.	PERFORMANCE SUMMARY F	_1
	Table:	. 1
	1 Performance Summary F-2	
	2 Summary of Waste Transactions in the Double-Shell Tanks	
	3 Comparison of Projected Versus Actual Waste Volumes for	
	Hanford Facilities F-5	

WASTE TANK SUMMARY REPORT FOR MONTH ENDING APRIL 30, 1997

Note: Changes from the previous month are in bold print

I. WASTE TANK STATUS

Category	Quantity	Date of Last Change
Double-Shell Tanks ^c	28 double-shell	10/86
Single-Shell Tanks	149 single-shell	07/88
Assumed Leaker Tanks ^f	67 single-shell	7/93
Sound Tanks	28 double-shell 82 single-shell	1986 7/93
Interim Stabilized Tanks ^{b,d}	117 single-shell	1/97
Not Interim Stabilized ^f	32 single-shell	1/97
Intrusion Prevention Completed®	108 single-shell	09/96
Controlled, Clean, and Stable	36 single-shell	09/96
Watch List Tanks ⁸ Total	32 single-shell 6 double-shell 38 tanks	9/96 ^h 6/93

^{*} All 149 single-shell tanks were removed from service (i.e., no longer authorized to receive waste) as of November 21, 1980.

^b Of the 116 tanks classified as Interim Stabilized, 62 are listed as Assumed Leakers. The total of 116 Interim Stabilized tanks includes one tank (B-202) that does not meet current established supernatant and interstitial liquid stabilization criteria. (See Table I-1 footnotes item #2)

^c Six double-shell tanks are currently included on the Hydrogen Watch List and are thus prohibited from receiving waste in accordance with "Safety Measures for Waste Tanks at Hanford Nuclear Reservation," Section 3137 of the *National Defense Authorization Act for Fiscal Year 1991*, November 5, 1990, Public Law 101-510.

^d Of the 32 single-shell tanks on Watch Lists, 11 have been Interim Stabilized.

^e Of the 32 single-shell tanks on Watch Lists, 11 have completed Intrusion Prevention (this category replaced Interim Isolation). (See Appendix C for "Intrusion Prevention" definition).

f Five of these tanks are Assumed Leakers. (See Table H-1) Tank SX-102 was declared an Assumed Leaker in May, and reclassified as Sound in July, 1993. See "Waste Tank Investigations" section of the July 1993 report for more details.

^{*} See Section A tables for more information on Watch List Tanks. Eight tanks (A-101, S-102, S-111, SX-103, SX-106, U-103, U-105, and U-107) are currently on more than one Watch List.

h Dates for the Watch List tanks are "officially added to the Watch List" dates. (See Table A-1, Watch List Tanks, for further information.)

¹ The TY tank farm was officially declared Controlled, Clean, and Stable in March 1996. The TX tank farm and BX tank farms were declared CCS in September 1996. (BX-103 has been declared to have met current interim stabilization criteria, and is included in CCS - see also Appendix 1).

III. SURVEILLANCE AND WASTE TANK STATUS HIGHLIGHTS

1. Single-Shell Tanks Saltwell Jet Pumping (See Table E-6 footnotes for further information)

<u>Tank 241-BY-109</u> - Pumping resumed September 11, 1996, and was shut down in October in preparation for a transfer. Pumping resumed April 2, 1997. 3.1 Kgallons were pumped in April. A total of 157.1 Kgallons has been pumped from this tank.

Tank 241-T-104 - Pumping started March 24, 1996. The pump failed in August and was replaced; pumping resumed in September and 5.2 Kgallons were pumped in October. Pumping was suspended October 18 for flammable gas issues, and resumed January 4, 1997. 1.6 Kgallons were pumped in January, no pumping was done in February and March, pending completion of the transfer line pressure test. Pumping resumed April 17, and 3.1 Kgallons were pumped from this tank in April. A total of 93.7 Kgallons has been pumped from this tank.

Tank 241-T-110 - Approval to reclassify this tank as a Facility Group 3, to allow pumping per the flammable gas JCO Standing Order, was requested February 18; verbal approval received April 25. Lance and saltwell screen installed on March 25 in preparation for pumping.

2. Single-Shell Tank TPA Interim Stabilization Milestones

All M-41-xx Milestones are being renegotiated.

3. Tank Waste Remediation System Safety Initiatives

The U. S. Secretary of Energy has directed that six safety initiatives be implemented in the Tank Waste Remediation System Program to accelerate the mitigation/resolution of the high priority waste tank safety issues at the Hanford Site. Forty-two milestones were established for accomplishing the initiatives.

No Safety Initiatives were scheduled to be completed this month.

4. Characterization Progress Status (See Appendix J)

Characterization is understanding the Hanford tank waste chemical, physical, and radiological properties to the extent necessary to ensure safe storage and interim operation, and ultimate disposition of the waste.

Characterization Progress for April:

All four single-shell tanks in the 241-T-200 series were push mode sampled in April, as shown on the Characterization Chart (J-1). Three of these tanks were previously unsampled for Characterization purposes. Tank 241-U-103 was also push mode sampled this month. Three grab samples were taken, including a C-Farm drywell. Tank 241-BX-104 was vapor sampled.

Three new Tank Characterization Reports were issued in April for tanks 241-BY-107, S-111, and U-106. Reports are available in the Tank Characterization Safety and Resource Center, 200 East Area, 2750E/C-135.

5. Gas Release Event in Double-Shell Tank

Tank AN-105 had a gas release event on April 5, beginning at 10 pm. The event ended at approximately 1:30 am on April 6, 1997. The highest hydrogen concentration in the tank vapor space was 0.7% hydrogen. The tank experienced a .35-inch level decrease.

Tank pressure remained stable at -1.6 to -1.8 inches water gauge. No significant waste temperature changes have occurred.

Off Normal Occurrence Report RL-PHMC-TANKFARM-1997-0036 was issued May 7, 1997.

APPENDIX A

WASTE TANK SURVEILLANCE MONITORING TABLES

TABLE A-2. ADDITIONS/DELETIONS TO WATCH LISTS BY YEAR April 30, 1997

Added/Deleted dates may differ from dates that tanks were officially added to the Watch Lists. (See Table A-1).

									Total Tanks (1)			
	Fелто	cyanide	Hyd	irogen	Org	anics	High Heat	SST	DST	Total		
1/91 Original List -Response to Public Law 101-510	23		23		8	200	1	47	5			
Added 2/91 (revision to Original List)	1	T-107						1				
Total - December 31, 1991 Added 8/92	24		23		- 8		1	48	5	A company of the comp		
	9000007****		1	AW-101	Outoficeresses		0600 T00000000000000		1			
Total - December 31, 1992 Added 3/93	24		24	9169 19232 - 000	В	11777	1	48	6	- 5		
Added 3/93 Deleted 7/93 Added 12/93	-4	(BX-110) (BX-111) (BY-101) (T-101)		(1) 40%	1	U-111		1 -4				
			1	(U-107)	100000000000000000000000000000000000000		\$500,000,000 000,000,000	0				
Total - December 31, 1993 Added 2/94	20		25		9	T-111	1	45	6	51		
Added 5/94					10	A-101 AX-102 C-102 S-111 SX-103 TY-104 U-103 U-105 U-203 U-204		4				
Deleted 11/94	-;	2 (BX-102) (BX-106)				0-204		-2				
Total - December 31, 1994, & December 31, 1995	18		25		20		1	48	6	54		
Deleted 6/96 Deleted 9/96	-14	(C-108) (C-109) (C-111) (C-112) (BY-103) (BY-104) (BY-105) (BY-106) (BY-107)						-12				
Total - April 30, 1997		(BY-108) (BY-110) (BY-111) (BY-112) (T-107) (TX-118) (TY-101) (TY-103) (TY-104)	25									

⁽¹⁾ Eight tanks are on more than one list: A-101, S-102, S-111, SX-103, SX-106, U-103, U-105, and U-107; therefore the total of tanks added or deleted will depend upon whether a tank is also on another list.

TABLE A-3. TEMPERATURE MONITORING IN WATCH LIST TANKS (sheet 2 of 2)

Notes:

Unreviewed Safety Question(USO):

There is a USQ currently associated with all single-shell tanks, resulting in special controls required, and limiting the work in the tanks. Pumping is on hold until the DOE-RL approval is received for each tank.

Hydrogen/Flammable Gas:

Tanks which are suspected to have a significant potential for hydrogen/flammable gas generation, entrapment, and episodic release. The USQ associated with these tanks is due of the potential consequences of a radiological release resulting from a flammable gas burn, an event not analyzed in the SST Safety Analysis Report (SAR).

Organic Salts:

Single-shell tanks containing concentrations of organic salts ≥3 weight% of total organic carbon (TOC)(equivalent to 10 wt% sodium acetate). The USQ associated with these tanks is because it has been concluded there is a small potential for an organic nitrate accident. Double-shell tanks have >3 weight% TOC but are not on the Watch List because they contain mostly liquid, and there is no credible organic safety concern for tanks which contain mostly liquid.

High Heat:

Tanks which contain heat generating strontium-rich sludge and require drainable liquid to be maintained in the tank to promote cooling. Only tank C-106 is on the High Heat Watch List because in the event of a leak, without water additions the tank could exceed temperature limits resulting in unacceptable structural damage. The tank is cooled through evaporation in conjunction with active ventilation. Water is periodically added as evaporation takes place.

Active ventilation:

There are 15 single-shell tanks on active ventilation (eight are on the Watch List as indicated by an asterisk):

C-105	SX-107
C-106 *	SX-108
SX-101 *	SX-109 *
SX-102 *	SX-110
SX-103 *	SX-111
SX-104 *	SX-112
SX-105 *	SX-114
SX-106 *	

Note: A-104, 105 and 106 exhauster has been out of service since 1991 and is no longer considered actively ventilated. Although C-104 has a cascade line with C-105, it is not considered to be actively ventilated.

Footnotes:

- (1) Tank SX-109 has the potential for flammable gas accumulation only because other SX tanks vent through it.
- (2) Tank C-106 is on the Watch List because in the event of a leak without water additions the tank could exceed temperature limits resulting in unacceptable structural damage.
- (3) There are no in-waste temperatures for tanks AX-102 and B-103. The waste level in these tanks is lower than the lowest thermocouple in these trees. Temperatures in this table show the maximum in the tanks taken in the vapor space.

TABLE A-5. SINGLE-SHELL TANKS MONITORING COMPLIANCE STATUS

149 TANKS (Sheet 1 of 6) April 30, 1997

The following table indicates whether Single-Shell tank monitoring was in compliance with the requirements as specified in the applicable documents as of the last day of the applicable month:

NOTE:

All Watch List and High Heat tank temperature monitoring is in compliance. (5)

All Dome Elevation Survey monitoring is in compliance.

All Psychrometrics monitoring is in compliance (2). Drywell monitoring is done "as needed" (10). In-tank photos/videos are taken "as needed" (3)

LEGEND:	
(Shaded)	= in compliance with all applicable documentation
N/C	= noncompliance with applicable documentation
0/\$	= Out of Service
Neutron	= LOW readings taken by Neutron probe
POP	= Plant Operating Procedure, TO-040-650
MT/FIC/	= Surface level measurement devices
ENRAF	
OSR	= Operational Safety Requirements, SD-WM-OSR-005
OSD	= Operating Specifications Doc., OSD-T-151-00013, -00031
N/A	= Not applicable (not monitored, or no monitoring schedule)
None	= Applicable equipment not installed

	Tank Category		Temperature	Primary Leak	Surf	LOW Readings			
Tank	Watch High		Readings	Detection	-	(OSD)(6.8)			
Number	List	Heat	(5)	Source (6)	МТ	(OSR,OSD)	ENRAF	Neutron	
A-101	Х			LOW	None	None			
A-102				None	None		None	None	
A-103				LOW	None	None			
A-104		X		None	None	None		None	
A-105		X		None		None	None	None	
A-106				None	None	None		None	
AX-101	X			LOW	None	None		(11)	
AX-102	×			None		None	None	None	
AX-103	X			None	None	Ngpe		None	
AX-104				None	None	None		None	
B-101				None	None		None	None	
B-102				ENRAF	None	None		None	
B-103	X			None	None		None	0/6	
B-104				LOW		None	None	50000000000000000000000000000000000000	
B-105				row		None	None		
B-106				FIC	None		None	None	
B-107				None		Nane	None	None	
B-108				None	None		None	Nane	
B-109				None		None	None	None	
B-110				LOW		None	None		
B-111				LOW	None		None		
B-112				ENRAF	None	None		None	
B-201				MT		None	None	None	
B-202				MT		None	None	None	
B-203				MT		None	None	None	
B-204				MT		None	None	None	
BX-101				ENRAF	None	None		Ngne	
BX-102				None	O/S	None		None	
BX-103				ENRAF	None	None		None	
BX-104			None	ENRAF	None	None		None	
BX-105				None	None	None		None	
BX-106				ENRAF	None	None		None	
BX-107		ASSESSED BUILDING		ENRAF	None	None		None	

TABLE A-5. SINGLE-SHELL TANKS MONITORING COMPLIANCE STATUS 149 TANKS (Sheet 3 of 6)

	Tank Category		Temperature	Primary Leak	Surf	LOW Readings		
Tank Number	Watch List	High	Readings	Detection		(OSD)(6,8)		
		Heat	(5)	Source (6)	МТ	FIC	ENRAF	Neutron
SX-109 (4) SX-110	, х	X		None	200.007 (0.000.0010.00)	None	None	None
				None		None	None	None
SX-111 SX-112	200000000000000000000000000000000000000	X		None		None	None	None
SX-112		X		None		None	None	None
5X-113 5X-114	201000000000000000000000000000000000000	×		None		None	None	None
SX-115		•		None		None	None	None
T-101			None	None		None	None	None
T-102			None	None ENRAF	None	None		None
T-103			Mulie	None	None	None	000000000000000000000000000000000000000	None
T-104				LOW	None	None		None
T-105			None	None	None	None		
T-106				None	None	None		None
T-107				ENRAF	None	None None		None
T-108				ENRAF	None	None		None
T-109				None	None	None		None
T-110	×			LOW	None	None		None
T-111	Υ.			LOW	None	None		
T-112				ENRAF	None	None		
T-201				MT	TONO	None	None	None
T-202				MT		None	None	None
T-203				None		None	None	None None
T-204				MT		None	None	
TX-101			None	ENRAF	None	None	3,012	None
TX-102				LOW	O/S	None		None
TX-103				None	None	0/6		None
TX-104				None	None	None		None
TX-105	X			None		None		None (9)
TX-106				LOW		None		
TX-107				None	None	0/8		None
TX-108				None	None	D/S		None
TX-109				LOW	None	None		
TX-110			None	LOW		None		
TX-111				LOW		None		
TX-112				Low		None		
TX-113				LOW		None		
TX-114			None	LOW		None		
TX-115				LOW		None		
TX-116			None	None		None		None
TX-117			None	LOW		None		
TX-118				LOW	None	None		
TY-101	_			None	None	None		None
TY-102				ENRAF	None	None		None
TY-103 TY-104				LOW	None	None		
TY-104				ENRAF	None	None		None
TY-105				None	O/S	None		None
J-101	2000 000 000 000 000 000 000 000 000 00		0.0000000000000000000000000000000000000	None	0/5	None		None
J-101 J-102				MT		None	None	None
J-102 J-103	×			LOW	None	None		
J-103 J-104	A		11-2-	ENRAF	None	None		
)-105	×		None	None	\1=	None	None	None
J-106	Î		11240421000210002100101010102021	ENRAF	None	None :		

TABLE A-5. SINGLE-SHELL TANKS MONITORING COMPLIANCE STATUS -149 TANKS (Sheet 5 of 6)

Footnotes:

1. All SSTs have either manual tape, FIC, (or ENRAF), zip cord, or a combination of these surface level measuring devices.

ENRAF gauges are being installed to replace FICs, with the exception of C-106, which has both an ENRAF and an FIC. The ENRAF gauges are being connected to TMACS, but many are currently being read manually from the field. See Table A-7 for list of ENRAF installations.

- 2. High heat tanks have active exhausters; psychrometrics can be taken in the high heat tanks. Psychrometric readings are taken on an "as needed" basis with the exception of tanks C-105/106. Hanford Federal Facility Agreement and Consent Order," Washington State Department of Ecology, U. S. Environmental Protection Agency, and U. S. Department of Energy, "Fourth Amendment 1994 (Tri-Party Agreement) requires psychrometric readings to be taken in C-105/106 on a monthly frequency.
- 3. In-tank photographs and videos are requested on an "as needed" basis.
- 4. Two tanks are on both category lists (C-106 and SX-109).
- 5. Temperature readings may be regulated by OSD or POP. Temperatures cannot be obtained in 13 low heat load tanks (see Table A-4). The OSD does not require readings or repair of out-of service thermocouples for the low heat load (≤40,000 Btu/h) tanks. However, the POP requires that attempts are to be made semiannually in January and July to obtain readings for these tanks.

Temperatures for many tanks are monitored continuously by TMACS; see Table A-8, TMACS Monitoring Status.

- 6. Document WHC-OSD-T-151-00031, "Operating Specifications for Tank Farm Leak Detection," requires that single-shell tanks with the surface level measurement device contacting liquid, partial liquid, or floating crust surface, will be monitored for leak detection on a daily basis. Tanks with a solid surface will be monitored for leak detection on a weekly basis by taking neutron scan data from a Liquid Observation Well (LOW), if an LOW is present. Tanks with a solid surface but without LOWs will not be monitored for leak detection if the tank has been interim stabilized, until an LOW is installed. Non-interim-stabilized tanks will have drywell surveys taken as a backup on a monthly basis if surface or interstitial level measurement equipment is unavailable. The OSD specifies what leak detection methods are to be used for each tank, and the requirements if the readings are not taken on the required frequency or if equipment is out of service.
- 7. Leak detection for the catch tanks is performed by monitoring for the buildup of liquid in the secondary containment (for most tanks with secondary containment) or for decrease in the liquid level for those tanks without secondary containment or secondary containment monitoring.

Tanks 240-S-302 and 241-S-302-A are monitored for intrusions only, and are not subject to leak detection monitoring requirements until liquid is present above the intrusion level.

Weight Time Factor is the surface level measuring device currently used in A-417, A-350 and 244-A-Tank/Sump. DCRT CR-003 is inactive and measured in gallons.

8. Document WHC-SD-WM-TI-605, REV. 0, dated January 1994, describes the rationale for Liquid Observation Well (LOW) installation priority. This priority is based on tank leak status, tank surface condition, and tank stabilization status. Also included is a listing of tanks with the waste level being below two feet which have no priority assigned because no effort will be made to install LOWs in the near future. LOW probes are unable to accurately monitor interstitial liquid levels less than two feet high.

TABLE A-6. DOUBLE-SHELL TANKS MONITORING COMPLIANCE STATUS 28 TANKS (Sheet 1 of 2) April 30, 1997

The following table indicates whether Double-Shell tank monitoring was in compliance with the requirements as specified in the applicable documents as of the last day of the applicable month.

NOTE:

Dome Elevation Surveys are not required for DSTs.

Psychrometrics and in-tank photos/videos are taken "as needed" (2)

LEGEND: (Shaded) = In compliance with all applicable documentation N/C = Noncompliance with applicable documentation FIC/ENRAF = Surface level measurement devices M.T. OSR = SD-WM-OSR-016, SD-WM-OSR-004 OSD = OSD-T-151-0007, OSD-T-151-0031 None = no M.T., FIC or ENRAF installed = Out of Service O/S W.F. = Weight Factor Rad. = Radiation

						1	Radiation Readin	gs	
Tank		Temperature Readings (3)	Su	arface Level Read	•		Leak Detection Pits (4) (OSR, OSD)		
Number	Watch List	(OSD)	M.T.	FIC	ENRAF	W.F.	Rad. (8)	(OSD)	
AN-101				None			(8)		
AN-102					None		(8)		
AN-103	X			None			(8)		
AN-104	X		0/8	Name			(8)		
AN-105			0/8	Nore			(8)		
AN-106					None		(8)		
AN-107					None		(e)		
AP-101					None	0/\$	(19)		
AP-102					None	0/5	(8)		
AP-103					None	0/5	(8)		
AP-104			0/8		None	0/8	(8)		
AP-105					None	0/\$	(E)		
AP-106					None	0/5	(8)		
AP-107					None	0/5	(8)		
AP-108					None	0/6	(8)		
AW-101	X			None			(8)		
AW-102					(6)		(8)		
AW-103				None			(8)		
AW-104				None			(8)		
AW-105				None			(8)		
AW-106				None	la de la companie de		(8)		
AY-101				None			(8)	(6)	
AY-102				O/S	None		(6)		
AZ-101			O/S	None	******		(8)	(5)	
AZ-102				0/5	None		(8)	(6) (5)	
SY-101	X		0/8	None			0/S (7)	(9)	
SY-102				None			ma (1)		
SY-103	Х		O/S	None			O/S (7)		
Totals: 28 tanks	6 Watch List Tanks	N/C: 0	N/C: 0	N/C: 0	N/C: O	N/C: 0	N/C: 0	N/C: 0	

TABLE A-7. ENRAF SURFACE LEVEL GAUGE INSTALLATION AND DATA INPUT METHODS

April 30, 1997

								0, 1997						
LEGEND	CASS	= Compi	ute	r Automa	ted Surveillar	nce System								
	SACS = Surveillance Analysis Computer System													
	TMACS = Tank Monitor and Control System													
	Auto # Automatically entered into TMACS and electronically transmitted to SACS													
	Manual	= EITHER	Rn	nanualiy e	entered into C	ASS by fie	ld	operators	and electron	ically transm	itte	d to SA	cs	
		OR man	ual	ly entered	directly into	SACS by s	ur	veillance	personnel, fro	m Field Data	sl	neets		
EAST A	AREA							WEST	AREA					
Tank	Installed	Input		Tank	Installed	Input		Tank	Installed	Input		Tank	Installed	Input
i	ì	1 '		8				88	i _			8	4 _	
No.	Date	Method	888 888	No.	Date	Method	88	No.	Date	Method		No.	Date	Method
A-101	09/95	Manual	333 333	B-201	<u> </u>		***	S-101	02/95 05/95	Manual		TX-101	11/95	Auto
A-102	07/96	Manual	2000 2000	B-202 B-203	<u> </u>		88	S-102 S-103	05/95	Manual Auto		TX-102 TX-103	05/96 12/95	Auto
A-103 A-104	05/96	Manual	2003 2003	B-204				S-103	- 03/34	Auto	988	TX-103	03/96	Auto
A-105	03/\$0	IVIAITUAI	800 888	BX-101	04/96	Auto	***	S-105	07/95	Manual		TX-105	04/96	Auto
A-106	01/96	Manual		BX-102	06/96	Auto	***	S-106	06/94	Auto		TX-106	04/96	Auto
AN-101	08/96	Auto		BX-103	04/96	Auto	×	S-107	06/94	Auto		TX-107	04/96	Auto
AN-102			88	BX-104	05/96	Auto		S-108	07/95	Manual		TX-108	04/96	Auto
AN-103	08/95	Auto		BX-105	03/96	Auto		S-109	08/95	Manual		TX-109	11/95	Auto
AN-104	08/95	Auto	***	BX-106	07/94	Auto	***	S-110	08/95	Manual		TX-110	05/96	Auto
AN-105	08/95	Auto		BX-107	06/96	Auto		S-111	08/94	Auto		TX-111	06/96	Auto
AN-106	<u> </u>			BX-108	05/96	Auto		S-112	05/95	Manual		TX-112	05/96	Auto
AN-107	 		**	BX-109	08/95	Auto	8	SX-101	04/95	Manual	***	TX-113	05/96	Auto
AP-101				BX-110	06/96	Auto		SX-102	04/95	Manual		TX-114	05/96	Auto
AP-102	1			BX-111	05/96	Auto		SX-103	04/95	Manua!		TX-115	05/96	Auto
AP-103				BX-112	03/96	Auto		SX-104	05/95	Manual		TX-116	05/96	Auto
AP-104				BY-101			*	SX-105	05/95	Manual	88	TX-117	06/96	Auto
AP-105				BY-102			8	SX-106	08/94	Auto		TX-118	03/96	Auto
AP-106				BY-103	12/96	Manual		SX-107			*	TY-101	07/95	Auto
AP-107				BY-104				SX-108			***	TY-102	09/95	Auto
AP-108			 	BY-105				SX-109				TY-103	09/95	Auto
AW-101	08/95	Manuai	 	BY-106				SX-110				TY-104	06/95	Auto
AW-102	05/96	Manual		BY-107				SX-111				TY-105	12/95	Auto
AW-103	05/96	Manual	888	BY-108				SX-112				TY-106	1 2/95	Auto
AW-104	01/96	Manual		BY-109	<u> </u>			SX-113				U-101		
AW-105	06/96	Manual		BY-110			88	SX-114				U-102	01/96	Manusi
AW-106	06/96	Manual		BY-111				SX-115				U-103	07/94	Auto
AX-101	09/95	Manual	888	BY-112			88	SY-101	07/94	Auto		U-104		
AX-102				C-101				SY-102	06/94	Manual		U-105	07/94	Auto
AX-103	09/95	Manual		C-102				SY-103	07/94	Manual		U-106	08/94	Auto
AX-104	10/96	Manual	***	C-103	08/94	Auto	888	T-101	05/95	Manual		U-107	08/94	Auto
AY-101	03/96	Manual	2.15	C-104	05/00			T-102	06/94	Auto		U-108	05/95	Manual
AY-102	08/06	Manual	\$8.83 86.61	C-105 C-106	05/96	Manual	888	T-103 T-104	07/95 12/95	Manual	3883 3883	U-109	07/94	Auto
AZ-101	08/96	Manual	38388 38388	C-106 C-107	02/96	Auto	***	T-104		Manual Manual	2000 2000	U-110	01/96	Manual
AZ-102 B-101	ļ		883	C-108	04/95	Auto	888	T-106	07/95 07/95		8888 8888	U-111	01/96	Manuai
B-101	02/95	Manual		C-108				T-106	06/94	Manual Auto	888 888	U-112 U-201	ļ 	
B-102	02/30	171411461		C-110				T-10B	10/95	Manual		U-202		
B-104	 		***	C-111				T-109	09/94	Manual		U-203		
B-105			***	C-112	03/96	Manual		T-110	05/95	Auto	***	U-204		
B-106	†			C-201			m	T-111	07/95	Manual	***			
B-107				C-202				T-112	09/95	Manual		-		
B-108	 			C-203				T-201			***			
B-109				C-204				T-202						
B-110	02/97	Manual						T-203						
B-111	02/97	Manual		,,				T-204			***	·		
B-112	03/95	Manual	***								***			
	* Aran: 41		80.08	L				7 - 2 - 1 344			0.33			L

106 ENRAFs installed: 57 automatically entered into TMACS, 49 manually entered into CASS

Total East Area: 41

Total West Area: 65

APPENDIX B

DOUBLE SHELL TANK WASTE TYPE AND SPACE ALLOCATION

Table B-2. Double Shell Tank Waste Inventory for April 30, 1997

TANKS	INVENTORY	SOLIDS	TYPE	LEFT
101AW=	1125	222	DSSF	15
102AW=	91	3 3	DN	1049
103AW=	512	363	NCRW	628
104AW=	1119	26 7	ÐΝ	21
105AW=	438	286	NCRW	702
106AW=	909	224	DSSF	231
101AY=	903	94	DC	7 7
102AY=	83 3	30	DΝ	147
101AZ=	907	35	NCAW	73
102AZ=	904	95	NCAW	76
101AN=	117	33	DN	1023
102AN=	1075	89	CC	65
103AN=	95 5	410	DSS	185
104AN=	1055	449	DSSF	85
105AN=	1127	489	DSSF	13
106AN=	219	17	CC	921
107AN=	1055	247	CC	85
101SY=	1114	41	CC	26
102SY=	633	123	DN/PT	507
103SY=	744	362	CC	396
101AP=	1115	0	DSSF	25
102AP=	1095	0	CP	45
103AP=	23	1	DN	1117
104AP=	26	0	DΝ	1114
105AP=	166	154	DN	974
106AP=	327	0	DN	813
107AP=	29	0	DN	1111
108AP=	255	0	DC	885
TOTAL=	18871		TOTAL=	12409

NOTE: Solids Adjusted to Most Current Available Da	ata
NOTE: All Volumes in Kilo-Gallons (Kgals)	

TOTAL DST SPACE	AVAILABLE
NON-AGING =	27360
AGING =	3920
TOTAL=	31280

DST INVENTOR	CHANGE
03/97 TOTAL	18814
04/97 TOTAL	18871
INCREASE	57

WATCH LIST SPACE	
101AW=	15
101SY=	26
103SY=	396
103AN=	185
104AN=	85
105AN≃	13
TOTAL=	720
SEGREGATED SPACE	E IDC CC CD AMI

SEGREGATED SPACE	E IDC CC CD AMI
	E (DC,CC,CF,AVV)
102AP=	45
108AP=	885
101AY=	77
102AN=	65
106AN=	921
107AN=	85
101AZ=	73
102AZ=	76
TOTAL=	2227

WASTE RECEIVER SPACE	
101AN (200E/DC)=	1023
102SY (200W/DN)=	507
106AP (200E/DN)=	813
TOTAL=	2343

USABLE SPACE	
101AP=	25
103AP=	1117
104AP=	1114
105AP=	974
107AP=	1111
102AW=	1049
103AW=	628
104AW=	21
105AW=	702
106AW=	231
102AY=	147
TOTAL=	7119
EVAP. OPERATIONS	-1140
SPARE SPACE	-2280
USABLE LEFT=	3699

USABLE SPACE CHANGE	
03/97 TOTAL SPACE	3747
04/97 TOTAL SPACE	3699
CHANGE=	-48

WASTE RECEIVER SPACE	E CHANGE
03/97 TOTAL SPACE	2343
04/97 TOTAL SPACE	2343
CHANGE=	0

Inventory Calculation by Waste Type:

COMPLEXED WASTE		
102AN=	986 (CC)	
106AN=	202 (CC)	
107AN=	808 (CC)	
101SY=	1073 (CC)	
103\$Y=	382 (CC)	
101AY=	809 (DC)	
108AP=	255 (DC)	
TOTAL DC/CC=	4515	
TOTAL SOLIDS=	850	

NCRW SOLIDS (PD)		
103AW=	363	
105AW=	286	
TOTAL=	649	

PFP SOLIDS (PT)		
102SY≖	123	
TOTAL=	123	

CONCENTRATED PHOSPHATE (CP)		
102AP=	1095	
TOTAL=	1095	

DILUTE WASTE	(DN)
103AP=	22
104AP=	26
105AP=	12
106AP=	327
107AP=	29
101AN=	84
102AW=	58
103AW=	149
104AW=	852
105AW=	152
102AY=	803
102SY≃	510
TOTAL DN=	3024
TOTAL SOLIDS=	518

NCAW (AGING WA	STE)
(@ 5M Na)	
101AZ=	791
102AZ=	` 434
TOTAL @ ~5M Na=	1225
TOTAL DN=	456
TOTAL SOLIDS=	130

DSS/DSSF	
101AP=	1115
103AN=	545
104AN=	606
105AN≃	638
101AW=	903
106AW=	685
TOTAL DSS/DSSF=	4492
TOTAL SOLIDS=	1794

GRAND TOTALS	
NCRW SOLIDS=	649
DST SOLIDS=	3162
PFP SOLIDS=	123
AGING SOLIDS=	130
CC=	3451
DC=	1064
CP=	1095
NCAW=	1681
DSS/DSSF=	4492
DILUTE=	3024
TOTAL=	18871

INV0497




FIGURE B-1. TOTAL DOUBLE-SHELL TANK INVENTORY

APPENDIX C

TANK AND EQUIPMENT CODE AND STATUS DEFINITIONS

WASTE TYPES

Aging Waste (AGING)

High level, first cycle solvent extraction waste from the PUREX plant (NCAW)

Concentrated Complexant (CC)

Concentrated product from the evaporation of dilute complexed waste.

Concentrated Phosphate Waste (CP)

Waste originating from the decontamination of the N Reactor in the 100 N Area. Concentration of this waste produces concentrated phosphate waste.

Dilute Complexed Waste (DC)

Characterized by a high content of organic carbon including organic complexants: ethylenediaminetetra-acetic acid (EDTA), citric acid, and hydroxyethyl-ethylenediaminetriacetic acid (HEDTA), being the major complexants used. Main sources of DC waste in the DST system are saltwell liquid inventory (from SSTs).

Dilute Non-Complexed Waste (DN)

Low activity liquid waste originating from T and S Plants, the 300 and 400 Areas, PUREX facility (decladding supernatant and miscellaneous wastes), 100 N Area (sulfate waste), B Plant, saltwells, and PFP (supernate).

Double-Shell Slurry (DSS)

Waste that exceeds the sodium aluminate saturation boundary in the evaporator without exceeding receiver tank composition limits. For reporting purposes, DSS is considered a solid.

Double-Shell Slurry Feed (DSSF)

Waste concentrated just before reaching the sodium aluminate saturation boundary in the evaporator without exceeding receiver tank composition limits. This form is not as concentrated as DSS.

Non-complexed (NCPLX)

General waste term applied to all Hanford Site (NCPLX) liquors not identified as complexed.

PUREX Decladding (PD)

PUREX Neutralized Cladding Removal Waste (NCRW) is the solids portion of the PUREX plant neutralized cladding removal waste stream; received in Tank Farms as a slurry. NCRW solids are classified as transuranic (TRU) waste.

PFP TRU Solids (PT)

TRU solids fraction from PFP Plant operations.

Drainable Interstitial Liquid (DIL)

Interstitial liquid that is not held in place by capillary forces, and will therefore migrate or move by gravity. (See also Section 4)

Supernate

The liquid above the solids in waste storage tanks. (See also Section 4)

Ferrocvanide

A compound of iron and cyanide commonly expressed as FeCN. The actual formula for the ferrocyanide anion is [Fe(CN)₆]⁴.

control status, remove abandoned equipment, and place reusuable equipment in compliant storage; and "Stable" - remove pumpable liquids from the SSTs and IMUSTs and isolate the tanks.

TANK INTEGRITY

Sound

The integrity classification of a waste storage tank for which surveillance data indicate no loss of liquid attributed to a breach of integrity.

Assumed Leaker

The integrity classification of a waste storage tank for which surveillance data indicate a loss of liquid attributed to a breach of integrity.

Assumed Re-Leaker

A condition that exists after a tank has been declared as an "assumed leaker" and then the surveillance data indicates a <u>new</u> loss of liquid attributed to a breach of integrity.

TANK INVESTIGATION

Intrusion

A term used to describe the infiltration of liquid into a waste tank.

SURVEILLANCE INSTRUMENTATION

Drywells

Drywells are vertical boreholes with 6-inch (internal diameter) carbon steel casings positioned radially around SSTs. These wells range between 50 and 250 feet in depth, and are monitored between the range of 50 to 150 feet. The wells are sealed when not in use. They are called drywells because they do not penetrate to the water table and are therefore usually "dry." There are 759 drywells.

Monitoring is done by gamma radiation or neutron-moisture sensors to obtain scan profiles of radiation or moisture in the soil as a function of well depth, which could be indicative of tank leakage.

Two single-shell tanks (C-105 and C-106) are currently monitored monthly by gamma radiation sensors. The remaining drywells are monitored on request by gamma radiation sensors. Monitoring by neutron-moisture sensors is done only on request.

Laterals

Laterals are horizontal drywells positioned under single-shell waste storage tanks to detect radionuclides in the soil which could be indicative of tank leakage. These drywells can be monitored by radiation detection probes. Laterals are 4-inch inside diameter steel pipes located 8 to 10 feet below the tank's concrete base. There are three laterals per tank. Laterals are located only in A and SX farms. There are currently no functioning laterals and no plan to prepare them for use.

Surface Levels

The surface level measurements in all waste storage tanks are monitored by manual or automatic conductivity probes, and recorded and transmitted or entered into the Computer Automated Surveillance System (CASS).

Automatic FIC

An automatic waste surface level measurement device is manufactured by the Food Instrument Company (FIC). The instrument consists of a conductivity electrode (plummet) connected to a calibrated steel tape, a steel tape reel housing and a controller that automatically raises and lowers the plummet to obtain a waste surface level reading. The controller can provide a digital display of the data and also transmit the reading to the CASS. Some tanks have gauges connected to CASS and others are read manually. FICs are being replaced by ENRAF detectors (see below).

<u>IP</u> Intrusion Prevention Completed

IS Interim Stabilized

MT/FIC/ENRAF Manual Tape, Food Instrument Corporation, ENRAF Corporation (surface level measurement

devices)

OSD Operating Specifications Document

OSR Operational Safety Requirements

PI Partial Interim Isolated

SAR Safety Analysis Reports

SHMS Standard Hydrogen Monitoring System

TMACS Tank Monitor and Control System

TPA Hanford Federal Facility Consent and Compliance Order, "Washington State Department of Ecology,

U. S. Environmental Protection Agency, and U. S. Department of Energy," Fourth Amendment, 1994

(Tri-Party Agreement)

USQ Unreviewed Safety Question

Wyden Amendment "Safety Measures for Waste Tanks at Hanford Nuclear Reservation," Section 3137 of the National Defense Authorization Act for Fiscal Year 1991, November 5, 1990, Public Law 101-510.

4. INVENTORY AND STATUS BY TANK - VOLUME CALCULATIONS AND DEFINITIONS FOR TABLE E-6 (SINGLE-SHELL TANKS)

COLUMN HEADING	VOLUME CALCULATIONS/DEFINITIONS
Total Waste	Solids volume plus Supernatant liquid. Solids include sludge and saltcake (see definitions below) Supernatant Liquid Drainable Liquid Remaining minus Drainable Interstitial. Supernate is the clear liquid floating on the surface of the waste. Supernate is usually derived by subtracting the solids level measurement from the liquid level measurement. In some cases, the supernatant volume includes floating solid crusts because their volume cannot be measured. In-tank photographs or videos are useful in estimating the liquid volumes; the area of solids covered and the average depth can be estimated.
Drainable Interstitial Liquid	Drainable Liquid Remaining minus Supernate. Drainable interstitial liquid is calculated based on the saltcake and sludge volumes, using average porosity values or actual data for each tank, when available. Interstitial liquid is liquid that fills the interstitial spaces of the solids waste. Drainable interstitial liquid is calculated based on the saltcake and sludge volumes in the tank. The sum of the interstitial liquid contained in saltcake and sludge is the initial volume of drainable interstitial liquid. The volume reported as Drainable Interstitial Liquid is the initial volume of drainable interstitial liquid minus interstitial liquid removed by pumping.

APPENDIX D

TANK FARM CONFIGURATION, STATUS, AND FACILITY CHARTS




FIGURE D-2. DOUBLE-SHELL TANK INSTRUMENTATION CONFIGURATION

THE HANFORD TANK FARM FACILITY CHARTS (colored foldouts) ARE ONLY BEING INCLUDED IN THIS REPORT ON A QUARTERLY BASIS (i. e., months ending March 31, June 30, September 30, December 31)

NOTE: COPIES OF THE FACILITY CHARTS CAN BE OBTAINED FROM

DAN FOLEY, 200-E MULTI-MEDIA SERVICES,

373-3140, 2750E/C-143

ALMOST ANY SIZE IS AVAILABLE, AND CAN BE LAMINATED.

Charge code required

APPENDIX E

MONTHLY SUMMARY TANK USE SUMMARY PUMPING RECORD, LIQUID STATUS AND PUMPABLE LIQUID REMAINING IN TANK FARMS INVENTORY SUMMARY BY TANK FARM INVENTORY AND STATUS BY TANK

TABLE E-2. TANK USE SUMMARY April 30, 1997

	•				ISOLATED TA	· · · · ·		•
TANK <u>FARMS</u>	TANKS RECEIVING WASTE TRANSERS	SOUND	ASSUMED LEAKER	PARTIAL INTERIM	INTRUSION PREVENTION COMPLETED	CONTROLLED CLEAN, AND STABLE	INTERIM TABILIZED TANKS	
EAST								
A	0	3	3	2	4	0	5	
AN	7 (1)	7	0	0	0	-	Ō	
AP	8	8	0	0	0		0	
AW	6 (1)	6	0	0	0		0	
AX	0	2	2	1	3		3	
AY	2	2	0	0	0		0	
AZ	2	2	0	0	0		0	
В	0	6	10	0	16		16	(2)
BX	0	7	5	0	12	12	12	, ,
BY	0	7	5	5	7		8	
С	0	9	7	3	13		14	
Total	25	59	32	11	55	12	58	
WEST								
S	0	11	1	10	2		4	
SX	0	5	10	6	9		9	
SY	3 (1)	3	0	0	0		Ö	
Т	0	9	7	5	11		14	
TX	0	10	8	0	18	18	18	
TY	0	1	5	0	6	6	6	
V	0	12	4	9	7		8	
Total	3	51	35	30				
·······································	•	y.	၁၁	30	53	24	59	1 14 114
TOTAL	28	110	67	41	108	36	117	

⁽¹⁾ Six Double-Shall Tanks on the Hydrogen Tank Watch List are not currently receiving waste transfers (AN-103, 104, 105, AW-101, SY-101 and 103).

⁽²⁾ Includes tank B-202 which no longer meets established supernatant interstitial liquid stabilization criteria.

TABLE E-4. INVENTORY SUMMARY BY TANK FARM April 30, 1997

TANK EARM	TOTAL WASTE	AVAIL _SPACE	ļ													
EARM	WASTE	SPACE													SALT	
		U_AUL	_AGING	CC	CP	DC	DN	<u>DN/PD</u>	DN/PT	DSSE	NCPLX	TOTAL	DSS	SLUDGE	_CAKE	TOTAL
EAST																
A	1537	0	0	0	o	0	0	0	0	9	0	9	0	556	972	1528
AN	5603	2377	0	1996	0	0	84	0	0	1789	o	3869	410	1324	0	1734
AP	3036	6084	0	0	1095	255	416	0	0	1115	О	2881	0	155	0	155
AW	4194	2646	0	0	0	0	884	307	0	1503	О	2694	0	1389	111	1500
AX	906	0	0	3	0	0	0	0	0	0	О	3	0	19	884	903
AY	1736	224	0	0	0	809	803	0	0	0	0	1612	0	124	0	124
AZ	1811	149	1681	0	0	0	0	0	0	0	0	1681	0	130	0	130
3	2057	О	0	0	0	0	0	0	0	0	15	15	0	1697	345	2042
вх	1493	0	0	0	0	0	0	0	0	0	21	21	o	1351	121	1472
BY	4680	0	0	0	0	0	0	0	0	0	0	0	О	833	3847	4680
0	1976	0	0	0	0	1	o	O	0	0	171	172	, 0	1804	o	1804
Total	29029	11480	1681	1999	1095	1065	2187	307	0	4416	207	12957	410	9382	6280	16072
NEST									•							
3	5356	0	0	0	o	0	0	0	0	17	41	58	o	1166	4132	5298
SX	4419	0	o	0	0	1	0	0	0	o	62	63	0	1254	3102	4356
SY	2491	929	0	1451	0	o	0	0	562	0	0	2013	0	474	4	478
Г	1935	0	0	o	O	0	0	0	0	0	31	31	0	1904	0	1904
гх	7009	0	o	0	0	О	0	0	0	0	5	5	0	241	6763	7004
ſΥ	638	О	0	0	o	0	0	0	0	0	3	3	0	571	64	635
J	3550	0	0	0	O	0	0	0	0	31	137	168	o	638	2744	3382
otal	25398	929	0	1451	٥	1	0	ø	562	48	279	2341	ø	6248	16809	23057
OTAL	54427	12409	1681	3450	1095	1086	2187	307	562	4464	486	15298	410	15830	23089	39199

TABLE E-5. INVENTORY AND STATUS BY TANK - DOUBLE SHELL TANKS

April 30, 1997

		TANK	STATUS			_		LIQU	IID VOLUN	1E		SOLIDS V	OLUME	VOL	UME DETE	RMINATION	PHOTO	S/VIDEOS	1
								DRAIN-	DRAIN-	PUMP-						•			SEE
				EQUIVA-			SUPER-	ABLE	ABLE	ABLE	•					*			FOOTNOT
				LENT	TOTAL	AVAIL.	NATANT	INTER-	LIQUID	LIQUID				LIQUID	SOLIDS	SOLIDS	LAST	LAST	FOR
	WAST	TANK	TANK	WASTE	WASTE	SPACE	LIQUID	STIT.	REMAIN	REMAIN	DSS	SLUDGE	SALT	VOLUME	VOLUME	VOLUME	IN-TANK	IN-TANK	THESE
TANK	MATI	INTEGRITY	USE	INCHES	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)		CAKE	METHOD	METHOD	UPDATE	РНОТО		CHANGES
										F. D									
AY-101	DC	SOUND	DRCVR				i	<u>A</u>	Y TANK		i						i		
					903	77	809	4	813	809	0	94	0	FM	5	05/31/96	12/28/82		
AY-102	DN	SOUND	DRCVR	302.9	833	147	803	0	803	803	0	30	0	FM	s	05/31/96	04/28/81		
DOUBL	E-SHEL	L TANKS		TOTALS	1736	224	1612	4	1616	1612	ō	124	0	<u> </u>	7.1				
					-														·
								A	Z TANK	FARM ST	ATUS			_					
		SOUND	CWHT	329.8	907	73	872	0	872	872	0	35	0	FM	s	09/30/90	08/18/83		1
AZ-102	AGING	SOUND	DRCVR	328.7	904	76	809	4	813	809	0	95	0	FM	s	06/04/92	10/24/84		
DOUBL	E-SHEL	L TANKS		TOTALS	1811	149	1681	4	1685	1681	. 0	130	0						
									V TANK!	EADR OF				•				•	•
SY-101	cc	SOUND	OWNET	405.4		1			Y TANK		1				•		ı		
SY-101		SOUND	CWHT	405.1	1114	26	1073	0	1073	1073	0	41	0	FM	S		04/12/89		
SY-102		. =	DRCVR	230.2	633	507	562	0	562	562	0	71	0	FM	5	05/12/87	04/29/81		
51-103	CC	SOUND	CWHT	270.5	744	396	378	0	378	378	0	362	4	FM	s	06/30/96	10/01/85		(1)
3 DOUBL	E-SHEL	L TANKS	***	TOTALS	2491	929	2013	0	2013	2013	0	474	4						.
GRAND 1	TOTAL				18871	12409	14750	309	15059	14863	410	3596	115		·,··				

Note: +/- 1 Kgal differences are the result of computer rounding

Available Space Calculations Used in This Document

IOSR WHC-SD-WM-OSR-16 (AN, AP, AW, SY) WHC-T-151-00009 (Aging Waste)

1,127,500 (410 in.)(AW-Farm)

(Most Conservative)

AN, AP, AW, SY AY, AZ (Aging Waste)

Tank Farms

1,140,000 gal (414.5 in.) 980,000 gal (356.4 in:)

1,144,000 gal (416 in.)(AN, AP, SY)

1,000,000 gal (363.6 in.)(AY, AZ)

⁽¹⁾ Solids levels on these tanks were changed as the result of PNNL-11536, "Gas Retention and Release Behavior in Hanford DSTs," March 1997. Several devices were used to determine an average solids depth for these 5 tanks. SY-103 was actually updated to this sludge level by Process Memo earlier - see EP-0182-99, June 1996.

								UID VOLUI	7712		SOCIOS	VOLUME	- A OCOIN	E DETERMII	VA 11011	PHOTOS,		
						DRAIN-			DRAIN-	PUMP-				,				SEE
						ABLE	PUMPED		ABLE	ABLE								FOOTNOTES
			STABIL/	TOTAL	SUPER-	INTER-	THIS	TOTAL	LIQUID	LIQUID	Į	SALT	LIQUIDS	SOLIDS	SOLIDS	LAST	LAST	FOR
	WASTE	TANK	ISOLATION	WASTE	NATE	STIT.	MONTH	PUMPED	REMAIN	REMAIN	SLUDGE	CAKE	VOLUME	VOLUME	VOLUME	IN-TANK	IN-TANK	THESE
ANK	MAT'L.	INTEGRITY	STATUS	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	METHOD	METHOD	UPDATE	PHOTO	VIDEO	CHANGES
Y-101	NCPLX	ACMO I VO	IC (ID)CCC	40	ι.	_			NK FARM							ı		
	NCPLX	ASMD LKR	IS/IP/CCS	43	1	0	0.0	0.0	1	0	42	0	P	M		11/24/88	11/10/94	
	NCPLX	ASMD LKR	IS/IP/CCS	96	0	4	0.0	0.0	4	0	96	0	Р	М	04/28/82	09/18/85		1
		SOUND	IS/IP/CCS	68	6	0	0.0	0.0	6	0	62	0	Р	F	11/29/83	10/31/86	10/27/94	
	NCPLX	SOUND	IS/IP/CCS	99	3	30	0.0	17.4	33	27	96	0	F	F	09/22/89	09/21/89		
	NCPLX	SOUND	IS/IP/CCS	51	5	6	0.0	15.0	11	4	43	3	F	S	09/03/86	10/23/86		ĺ
	NCPLX	SOUND	IS/IP/CCS	38	0	0	0.0	14.0	0	0	38	0	MP	PS	08/01/95	05/19/88	07/17/95	
	NCPLX	SOUND	IS/IP/CCS	345	1	29	0.0	23.1	30	23	344	0	MP	P	09/18/90	09/11/90		[
	NCPLX	ASMD LKR	IS/IP/CCS	26	0	1	0.0	0.0	1	0	26	0	м	PS	07/31/79	05/05/94		
X-109	NCPLX	SOUND	IS/IP/CCS	193	0	13	0.0	8.2	13	8	193	0	FP	P	09/17/90	09/11/90		
	NCPLX	ASMD LKR	IS/IP/CCS	207	3	16	0.0	1.5	19	13	195	9	MP	M	10/31/94	07/15/94	10/13/94	ĺ
X-111	NCPLX	ASMD LKR	IS/IP/CCS	162	1	1	0.0	116.9	3	1	52	109	М	М	04/06/95	05/19/94	02/28/95	ĺ
X-112	NCPLX	SOUND	IS/IP/CCS	165	1	7	0.0	4.1	8	2	164	0	FP	P	09/17/90	09/11/90		

2 SING	LE-SHELL	TANKS	TOTALS:	1493	21	107	0.0	200.2	1 29	78	1351	121					7-20	
								BY TAI	NK FARM	STATUS								
Y-101	NCPLX	SOUND	IS/IP	387	l o	5	0.0	35,8	5	0	109	278	P	м	05/20/84	09/19/89		ı
Y-102	NCPLX	SOUND	IS/PI	277	0	11	0.0	159.0	11	0	0	277	MP	M		09/11/87	04/11/05	
Y-103	NCPLX	ASMD LKR	/Pt	400	0	15	0.0	98,9	15	9	5	395	MP	M	04/03/90		04/11/50	
Y-104	NCPLX	SOUND	IS/IP	406	0	18	0.0	329.5	18	0	40	366	P	M		04/27/83		<u>[</u>
Y-105	NCPLX	ASMD LKR	/PI	503	0	192	0.0	0.0	192	216	158	345	P	MP				l
Y-106	NCPLX	ASMD LKR	/PI	642	0	200	0.0	63.7	200	163	95	545 547	P		04/28/82			(c)
Y-107	NCPLX	ASMD LKR	IS/IP	266	0	25	0.0	56.4		0			•	MP		11/04/82		
	NCPLX	ASMD LKR	IS/IP	228	0	9	0.0	27.5	25		60	206	P	MP	04/28/82	•		
Y-109	NCPLX	SOUND	/PI	423	0	24	3.1	27.5 157.1	9	0	154	74	MP	M	04/28/82			
Y-110	NCPLX	SOUND	IS/IP	398	0	24 9			24	9	83	340	F	PS	08/30/91			(a)
/-111		SOUND	IS/IP		_		0.0	213.3	9	0	103	295	M	S	09/10/79			
	NCPLX	SOUND	IS/IP	459	0	0	0.0	313.2	0	0	21	438	Р	М	04/28/82			
2	HOLEX	SOUND	13/17	291	0	8	0.0	116.4	8	0	5	286	Р	М	04/28/82	04/14/88		
SING	LE-SHELL	TANKS	TOTALS:	4680	0	516	3.1	1570.8	516	397	833	3847				 	-	

Ġ

TABLE E-6. INVENTORY AND STATUS BY TANK - SINGLE-SHELL TANKS
April 30, 1997

	TANK S	TATUS			<u> </u>		LIQ	UID VOLU	ME .		SOLIDS VOLUME VOLUME DETERMINATION							
TANK	WASTE MAT'L.	TANK INTEGRITY	STABIL/ ISOLATION STATUS	WASTE	SUPER- NATE (Kgal)	DRAIN- ABLE INTER- STIT. (Kgal)	PUMPED THIS MONTH (Kgal)	TOTAL PUMPED (Kgal)	DRAIN- ABLE LIQUID REMAIN (Kgal)		SLUDGE (Kgal)	SALT CAKE (Kgal)	LIQUIDS VOLUME METHOD	SOLIDS VOLUME METHOD	SOLIDS VOLUME UPDATE	LAST IN-TANK PHOTO	LAST IN-TANK VIDEO	SEE FOOTNOTE FOR THESE CHANGES
	,,			•				CV TAI	MEZ EADAG	-							1,020	o, iii iii da
SX-101	DC	SOUND	/PI	456	1 1	145	0.0	0.0	NK FARM		٠.,		1 _					1
SX-102		SOUND	/PI	543	,	183	0.0	0.0	146 183	174	112	343	P	FP	04/28/82			(c)
	NCPLX	SOUND	/PI	652	1	232	0.0	0.0	233	216 272	117 115	426	P	М	04/28/82			l
SX-104	DSSF	ASMD LKR	/PI	614	ا ا	201	0.0	113.2	201	195	136	536 478	F F	s s	07/15/91 07/07/89			(c)
SX-105	DSSF	SOUND	/PI	683	0	261	0.0	0.0	261	299	73	610	P	s F	04/28/82			f_1
SX-106	NCPLX	SOUND	/PI	538	61	194	0.0	0.0	255	264	12	465	, ,	PS	10/28/80			(c)
SX-107	NCPLX	ASMD LKR	IS/IP	104	0	5	0.0	0.0	5	0	104	0	P	M	04/28/82	03/06/87		(c)
SX-108	NCPLX	ASMD LKR	IS/IP	87	0	5	0.0	0.0	5	o	87	0	Р	M	12/31/93			
SX-109	NCPLX	ASMD LKR	IS/IP	244	0	48	0.0	0.0	48	25	0	244	ء ا	м	01/10/96	05/21/86		
SX-110	NCPLX	ASMD LKR	IS/IP	62	0	0	0.0	0.0	0	0	62	0	м	PS	10/06/76	02/20/87		
X-111	NCPLX	ASMD LKR	IS/IP	1 25	0	7	0.0	0.0	7	0	125	0	м	PS	05/31/74	06/09/94		
	NCPLX	ASMD LKR	IS/IP	92	0	3	0.0	0.0	3	0	92	0	Р	M	04/28/82	03/10/87		
	NCPLX	ASMD LKR	IS/IP	26	0	0	0.0	0.0	0	0	26	0	Р	М	04/28/82	03/18/88		
	NCPLX	ASMD LKR	IS/IP	181	0	14	0.0	0.0	14	0	181	0	Р	М	04/28/82	02/26/87		
SX-115	NCPLX	ASMD LKR	IS/IP	12	0	0	0.0	0.0	0	0	12	0	P	М	04/28/82	03/31/88		
5 SING	LE-SHELL	TANKS	TOTALS:	4419	63	1298	0.0	113	1361	1445	1254	3102	<u> </u>				······································	
								TTAN	V PARIA C	TATIO								4
Γ-101	NCPLX	ASMD LKR	IS/PI	102	l 1	16	0.0	25.3	<u>K FARM S</u> 17	0	101	_	l -	•	احمديد	04/03/5-		i
r-102	NCPLX	SOUND	IS/IP	32	13	0	0.0	0.0	13	_	101 19	0	F P	S		04/07/93		
-103	NCPLX	ASMD LKR	IS/IP	27	4	0	0.0	0.0	4	13 0	23	0	r	FP FD	08/31/84	06/28/89		
-104	NCPLX	SOUND	/PI	365	o	38	3.1	93.7	38	35	365	0	r D	FP MP	11/29/83			.
-105	NCPLX	SOUND	IS/IP	98	0	23	0.0	0.0	23	17	98	0	, ,	F	04/31/97 05/29/87	06/29/89		(b)
r-106	NCPLX	ASMD LKR	IS/IP	21	2	0	0.0	0.0	2	,,	19	0	,	FP	04/28/82	05/14/87 06/29/89		}
-107	NCPLX	ASMD LKR	IS/PI	173	0	22	0.0	11.0	22	12	173	0	P	FP	1	07/12/84	05/00/00	İ
-108	NCPLX	ASMD LKR	IS/IP	44	0	0				' -	1/3	J	r	rr	03/31/80	07/12/84	UD/U9/96	

TABLE E-6. INVENTORY AND STATUS BY TANK - SINGLE-SHELL TANKS
April 30, 1997

	-	TANK S	STATUS					LIQ	UID VOLU	ME		SOLIDS	VOLUM	VOLUM	E DETERMI	NOTAN	PHOTOS/	VIDEOS	
						SUPER-	DRAIN- ABLE	PUMPED		DRAIN- ABLE	PUMP- ABLE					<u> </u>			SEE FOOTNOTES
				STABIL/	TOTAL	NATE	INTER-	THIS	TOTAL	LIQUID	LIQUID		SALT	LIQUIDS	SOLIDS	SOLIDS	LAST	LAST	FOR
		WASTE	TANK	ISOLATION		rianid	STIT.	MONTH	PUMPED	REMAIN	REMAIN	SLUDGE	CAKE	VOLUME	VOLUME	VOLUME	IN-TANK	IN-TANK	THESE
	TANK	MAT'L.	INTEGRITY	STATUS	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	METHOD	METHOD	UPDATE	PHOTO	VIDEO	CHANGES
									TY TA	NK FARM	STATUS								
	TY-101	NCPLX	ASMD LKR	IS/IP/CCS	118	0	o	0.0	8.2	0	0	118	o	l p	F	04/28/82	08/22/89		1
	TY-102	NCPLX	SOUND	IS/IP/CCS	64	0	14	0.0	6.6	14	0	0	64	P	FP	06/28/82	l ' '		
	TY-103	NCPLX	ASMD LKR	IS/IP/CCS	162	0	5	0.0	11.5	5	0	162	0	P	FP	07/09/82	1		
	TY-104	NCPLX	ASMD LKR	IS/IP/CCS	46	3	12	0.0	0.0	15	0	43	0	Р	FP	06/27/90	1		
	TY-105	NCPLX	ASMD LKR	IS/IP/CCS	231	0	0	0.0	3.6	0	0	231	0	P	M	04/28/82	1		
	TY-106	NCPLX	ASMD LKR	IS/IP/CCS	17	0	0	0.0	0.0	0	0	17	0	P	M	04/28/82	08/22/89		
ij	SINGL	E-SHELL T	ANKS	TOTALS:	638	3	31	0.0	29.9	34	0	571	64						<u> </u>
;									U TAN	K FARM	STATUS								
	J-101	NCPLX	ASMD LKR	IS/IP	25	3	o	0.0	0.0	3	0	22	0	l p	MP	04/28/82	06/19/79		I
	J-102	NCPLX	SOUND	/PI	374	18	126	0.0	0.0	144	160	43	313	P	MP	04/28/82			(c)
	J-103	NCPLX	SOUND	/PI	468	13	176	0.0	0.0	189	205	32	423	P	FP	04/28/82			(c)
	J-104	NCPLX	ASMD LKR	IS/IP	122	0	7	0.0	0.0	7	0	122	0	P	MP	04/28/82			""
	J-105	NCPLX	SOUND	/PI	418	37	142	0.0	0.0	179	192	32	349	FM	PS	09/30/78			(c)
	J-106	NCPLX	SOUND	/PI	226	15	68	0.0	0.0	83	85	26	185	F	PS	12/30/93			(c)
	J-107	DSSF	SOUND	/PI	406	31	147	0.0	0.0	178	183	15	360	F	s	12/30/93			(c)
	J-108	NCPLX	SOUND	/P1	468	24	172	0.0	0.0	196	209	29	415	F	s	12/30/93			(c)
	J-109	NCPLX	SOUND	/PI	463	19	163	0.0	0.0	182	205	48	396	F	F	06/30/96			(c)
	J-110	NCPLX	ASMD LKR	IS/PI	186	0	15	0.0	0.0	15	9	186	0	М	М	12/30/84	12/11/84		
	J-111	DSSF	SOUND	/PI	329	0	122	0.0	0.0	122	129	26	303	PS	FPS	02/10/84	06/23/88		(c)
	J-112	NCPLX	ASMD LKR	IS/IP	49	4	0	0.0	0.0	4	0	45	0	Р	MP	02/10/84	08/03/89		
	J-201	NCPLX	SOUND	IS/IP	5	1	0	0.0	0.0	1	0	4	0	м	s	08/15/79	08/08/89		
	J-202	NCPLX	SOUND	IS/IP	5	1	0	0.0	0.0	1	0	4	0	м	s	08/15/79	08/08/89		
	J-203	NCPLX	SOUND	IS/IP	3	1	0	0.0	0.0	1	0	2	0	м	5	08/15/79	06/13/89		1
	J-204	NCPLX	SOUND	IS/IP	3	1	0	0.0	0.0	1	0	2	0	м	s	08/15/79	06/13/89		
-	6 SING	LE-SHELL	TANKS	TOTALS:	3550	168	1138	0.0	0.0	1306	1377	638	2744				-		
_																			
	RAND	TOTAL			35556	548	5847	6.2	4379.5	6396	5745	12034	22974	l					

TABLE E-6. INVENTORY AND STATUS BY TANK - SINGLE-SHELL TANKS April 30, 1997

FOOTNOTES:

(c) Pumable Liquid Remaining totals were changed in this document in June 1996 to reflect information in WHC-SD-W236A-ES-012, "Multi-Function Waste Tank Facility Path Forward Engineering Analysis Tech. Task 3.3, SST Liquid Contents," dated May 1996. This reflected the new porosity numbers of 50% saltcake/21% sludge (vs old numbers of 45% saltcake/12-1/2% sludge). This document did not address Drainable Interstitial and Drainable Liquid Remaining totals; therefore, these totals remained unchanged in the Monthly Summary Report (Drainable Interstitial and Drainable Liquid Remaining totals in these tanks still reflect the old porosity numbers in the Monthly Summary Report).

Currently 22 tanks are affected: A-101, AX-101, BY-105, C-103, C-106, S-101, S-102, S-103, S-107, SX-101, SX-103, SX-105, SX-106, T-110, U-102, U-103, U-105, U-106, U-107, U-108, U-109, U-111. (Some tanks listed in the document were already the same as the Monthly Report; and some were later changed due to pumping or Interim Stabilization - these tanks are not included because their Drainables are correct.)

APPENDIX F PERFORMANCE SUMMARY

TABLE F-1. PERFORMANCE SUMMARY

(Sheet 2 of 2)


Footnotes:

INCREASES/DECREASES IN WASTE VOLUMES

- (1) Including flush
- (2) Sulfate waste is generated from ion exchange backflushing and sand filter clean out, resulting in sulfate waste.
- (3) Slurry increase/growth is caused by gas generation within the waste.
- (4) Aging waste tanks
- (5) Unknown waste gains or losses
- (6) Includes Tank Farms miscellaneous flushes
- (7) Liquid level measurement instrument changes from the automatic FIC to manual tape (and vice versa) result in unusual gains or losses because the manual tape may rest on an uneven crust surface giving a different reading from that of the automatic FIC.
- (8) Results from pumping of single-shell tanks to double-shell tanks.
- (9) Tracks waste being sent to the double-shell tanks from the "Precampaign Training Run." Evaporator procedures require a training run at least once per year. This also includes pressure testing and flushing of cross-site transfer lines.

WASTE VOLUME REDUCTION

- (10) Currently inoperative.
- Currently operative. The 242-A Evaporator-Crystallizer was started up March 1977, and shut down April 1989 because of regulatory issues, and remained shut down for subsequent upgrading. This evaporator operates under a vacuum, employing evaporative concentration with subsequent crystallization and precipitation of salt crystals (forming saltcake). The evaporator was restarted on April 15, 1994.



NOTE: The "Other" Catagory is For Waste Generations From, Evaporator Training, Pressure Tests and Cross-Site Transfers

FIGURE F-1. COMPARISON OF WASTE VOLUME GENERATIONS FOR HANFORD FACILITIES (All volumes in Kgals)

APPENDIX G

MISCELLANEOUS UNDERGROUND STORAGE TANKS AND SPECIAL SURVEILLANCE FACILITIES

			MONITORED		
<u> FACILITY</u>	<u>LOCATION</u>	RECEIVED WASTE FROM:	(Gallons)	<u>BY</u>	REMARKS
216-BY-201	BY Farm	TBP Waste Line	Unknown	NM	(216-BY)
241-A-302-B	A Farm	A-152 DB	5487	CASS/MT	Isolated 1985, Project B-138
					Interim Stabilized 1990, Rain intrusion
241-AX-151	N of PUREX	PUREX	Unknown	NM	Isolated 1985
241-B-301-B	B Farm	8-151, B-152, B-153, B-252 DB	22250	NM	Isolated 1985 (1)
241-B-302-B	B Farm	B-154 DB	4930	NM	Isolated 1985 (1)
241-BX-302-A	BX Farm	BR-152, BX-153, BXR-152, BYR-152 DB	840	NM	Isolated 1985 (1)
241-BX-302-B	BX Farm	BX-154 DB	1040	NM	Isolated 1985 (1)
241-BX-302-C	BX Farm	BX-155 DB	870	NM	Isolated 1985 (1)
241-C-301-C	C Farm	C-151, C-152, C-153, C-252 DB	10470	NM	Isolated 1985 (1)
241-CX-70	Hot Semi-	Transfer lines	Unknown	NM	Isolated, Decommission Project,
241-CX-72	Works	Transfer lines	650	NM	See Dwg H-2-95-501, 2/5/87
241-ER-311A	SW B Plant	ER-151 DB	Unknown	NM	Isolated
244-AR VAULT	A Complex	Between farms & B-Plant	Unknown	NM	Not actively being used. Systems
					activated for final clean-out.
244-BXR-TK/SMP-001	BX Farm	Transfer lines	7200	NM	Interim Stabilization 1985 (1)
244-BXR-TK/SMP-002	BX Farm	Transfer lines	2180	NM	Interim Stabilization 1985 (1)
244-BXR-TK/SMP-003	BX Farm	Trensfer lines	1810	NM	Interim Stabilization 1985 (1)
244-BXR-TK/SMP-011	BX Farm	Transfer lines	7100	NM	Interim Stabilization 1985 (1)
361-B-TANK	B Plant	Dreinage from B-Plant	Unknown	NM	Interim Stabilization 1985 (1)

18

LEGEND: DB - Diversion Box

DCRT - Double-Contained Receiver Tank

MT - Manual Tape

CASS - Computer Automated Survelliance System

TK - Tank

SMP - Sump

R - Usually denotes replacement

NM - Not Monitored

Total East Area inactive facilities

APPENDIX H LEAK VOLUME ESTIMATES

HNF-EP-0182-109

TABLE H-1. SINGLE-SHELL TANK LEAK VOLUME ESTIMATES (Sheet 2 of 3)

References:

- (a) Murthy, K.S., et al, June 1983, Assessment of Single-Shell Tank Residual Liquid Issues at Hanford Site, Washington, PNL-4688, Pacific Northwest Laboratory, Richland, Washington.
- (b) WHC, 1991a, Tank 241-A-105 Leak Assessment, WHC-MR-0264, Westinghouse Hanford Company, Richland, Washington.
- (c) WHC, 1991b, Tank 241-A-105 Evaporation Estimate 1970 Through 1978, WHC-EP-0410, Westinghouse Hanford Company, Richland, Washington.
- (d) Smith, D. A., January 1986, Single-Shell Tank Isolation Safety Analysis Report, SD-WM-SAR-006, Rev. 1, Westinghouse Hanford Company, Richland, Washington.
- (e) McCann, D. C., and T. S. Vail, September 1984, Waste Status Summary, RHO-RE-SR-14, Rockwell Hanford Operations, Richland, Washington.
- (f) Catlin, R. J., March 1980, Assessment of the Surveillance Program of the High-Level Waste Storage Tanks at Hanford, Hanford Engineering Development Laboratory, Richland, Washington.
- (g) Baumhardt, R. J., May 15, 1989, Letter to R. E. Gerton, U.S. Department of Energy-Richland Operations Office, Single-Shell Tank Leak Volumes, 8901832B R1, Westinghouse Hanford Company, Richland, Washington.
- (h) WHC, 1990a, Occurrence Report, Surface Level Measurement Decrease in Single-Shell Tank 241-AX-102, WHC-UO-89-023-TF-05, Westinghouse Hanford Company, Richland, Washington.
- (i) Groth, D. R., July 1, 1987, Internal Memorandum to R. J. Baumhardt, Liquid Level Losses in Tanks 241-C-201, -202 and -204, 65950-87-517, Westinghouse Hanford Company, Richland, Washington.
- (j) Groth, D. R. and G. C. Owens, May 15, 1987, Internal Memorandum to J. H. Roecker, *Tank 103-A Integrity Evaluation*, Westinghouse Hanford Company, Richland, Washington.
- (k) Campbell, G. D., July 8, 1988, Internal Memorandum to R. K. Welty, Engineering Investigation: Interstitial Liquid Level Decrease in Tank 241-SX-104, 13331-88-416, Westinghouse Hanford Company, Richland, Washington.
- (l) ERDA, 1975, Final Environmental Statement Waste Management Operations, Hanford Reservation, Richland, Washington, ERDA-1538, 2 vols., U.S. Energy Research and Development Administration, Washington, D.C
- (m) WHC, 1992a, Tank 241-SX-108 Leak Assessment, WHC-MR-0300, Westinghouse Hanford Company, Richland, Washington.
- (n) WHC, 1992b, Tank 241-SX-109 Leak Assessment, WHC-MR-0301, Westinghouse Hanford Company, Richland, Washington.
- (0) WHC, 1992c, Tank 241-SX-115 Leak Assessment, WHC-MR-0302, Westinghouse Hanford Company, Richland, Washington.
- (p) WHC, 1992d, Occurrence Report, Apparent Decrease in Liquid Level in Single Shell Underground Storage Tank 241-T-101, Leak Suspected; Investigation Continuing, RL-WHC-TANKFARM-1992-0073, Westinghouse Hanford Company, Richland, Washington.

APPENDIX I

INTERIM STABILIZATION STATUS CONTROLLED, CLEAN, AND STABLE STATUS

TABLE I-1. SINGLE-SHELL TANKS INTERIM STABILIZATION STATUS (sheet 2 of 2)

Footnotes:

- (1) These dates indicate when the tanks were actually interim stabilized. In some cases, the official interim stabilization documents were issued at a later date.
- Originally, seven tanks (B-104, B-110, B-111, BX-103, T-102, and T-112) did not meet current established supernatant and interstitial liquid interim stabilization criteria, but <u>did</u> meet the criteria in existence when they were declared interim stabilized.

B-110, B-111, U-110 were determined to have met current interim stabilization criteria, per WHC-SD-WM-ER-516-REV 0, "Interim Stabilization Status of SSTs B-104, B-110, B-111, T-102, T-112, and U-110," and WHC-SD-WM-ER-518-REV 0, "Investigation of Liquid Intrusion in 241-BX-103," both dated October 5, 1995.

B-104, BX-103, T-102, T-112 have been determined to meet current interim stabilization criteria as of September 30, 1996, per memo 9654456, J. H. Wicks to Dr. J. K. McClusky, DOE-RL.

<u>B-202</u> was determined to no longer meet the current established criteria for 200-series tanks due to a steady increase in the surface level indicating an ongoing intrusion based on a comparison of in-tank videos and subsequent evaluation in March 1996.

- (3) Original Interim Stabilization data are missing on four tanks: B-201, T-102, T-112, and T-102.
- (4) BX-110 was interim stabilized by Supernate Pumping in August 1985. Jet pumping began in December 1993 and soon stopped because of equipment failure. Due to low net volume pumped, major equipment failure, and ALARA, it was decided jet pumping would not resume. An in-tank video was taken in October 1994. Reevaluation after review of the video indicated 1.5 Kgallons of waste was pumped. (Almost 3 Kgallons of water flushes were needed to produce 1.5 Kgallons tank waste.)
- C-105 was interim stabilized administratively on October 30, 1995. No jet pumping occurred in this tank, nor does interstitial liquid level data exist for this tank. There are no diptubes or LOWs installed. Approximately 12 Kgallons of liquid waste was evaporated between May 1993 and October 1995. An in-tank video taken August 30, 1995, revealed a shallow supernatant pool surrounded by a 5-8 foot solids waste shore. The volume of supernate is estimated as 2 Kgallons. The tank currently meets the established criteria for declaring single-shell tanks Interim Stabilized.
- (6) T-107 was interim stabilized by Jet Pumping in May 1996. Pumping was completed in March, and an in-tank video taken in May showed no supernate visible on the surface. The surface has an irregular contour of mostly sludge, and the elevation differences between high and low points appear to be about four inches.
- (7) S-108 was interim stabilized by Jet Pumping in December 1996. Pumping was completed in September and an in-tank video taken in December showed no supernate visible on the surface of the waste, which appears to be saltcake. The video shows a relatively level surface with some caving and crowning. Total waste is 448.7 Kgallons, with drainable liquids 4.0 Kgallons and no pumpable liquids.
- (8) S-110 was interim stabilized by Jet Pumping in January 1997. Pumping was completed in July 1996, and an in-tank video taken in December showed no supernate visible on the surface of the waste, which appears to be saltcake. The level is not consistent and there appears to have been some caving and crowning. Total waste is 389.0 Kgallons, with drainable liquids 29.8 Kgallons and pumpable liquids 23.4 Kgallons.

TABLE I-3. SINGLE-SHELL TANKS CONTROLLED, CLEAN, AND STABLE (CCS) STATUS

April 30, 1997

The Controlled, Clean, and Stable (CCS) Mission Goals are to substantially reduce the operations and maintenance costs for the Single-Shell Tank Farms, to operate within the safety envelope, remove pumpable liquid wastes and contaminated soils/debris, and to achieve compliance with near-term regulatory requirements.

Facility	Completion Due	Completed	Comments
TY-Farm	December 29, 1995	December 29, 1995	Officially designated CCS in March 1996
BX-Farm	September 30, 1996	September 19, 1996	BX-103 has been declared to have met current interim stabilization criteria, and is therefore included in CCS
TX-Farm	September 30, 1996	September 17, 1996	
T-Farm (1)	June 30, 1997		
B-Farm (1)	September 30, 1997		
BY-Farm (1)	September 30, 1997		

⁽¹⁾ Controlled, clean, and stable activities have been deferred on these tank farms until funding is available

APPENDIX J CHARACTERIZATION PROGRESS STATUS

FIGURE J-1. CHARACTERIZATION PROGRESS STATUS CHART LEGEND (Sheet 2 of 2) April 30, 1997

200 East/West	The chart divides the two areas.		
Tank Farms	Each tank farm is represented by a rough schematic of the tank layout and a heading naming the farm.		
Circles	Tanks are depicted by a circle for single-shell tanks and a double circle for double-shell tanks.		
Boxes	A thin line box around a tank inside a tank farm denotes "Watch List" status, in concurrence with Table A-1 of this document.		
Numbers in Circles	The top number is the tank number. The number in parentheses is a weighted priority number, described in WHC-SD-WM-TA-164, "Tank Waste Characterization Basis." The numbers can be compared to each other to gain appreciation of relative priority: the higher the number, the greater the priority to sample and analyze.		
Underlined Numbers	If a number in parenthesis is underlined, it is denoted as a "Characterization Basis Tank," as described in WHC-SD-WM-TA-164, "Tank Waste Characterization Basis." These are key tanks taken from the priority list that are of principal interest to the Characterization Program.		
Circle Shading	The shading in the circle indicates the degree to which sampling and analysis are complete per requirements described in applicable Data Quality Objectives (DQOs). If blank, no characterization sampling has taken place. If fully shaded, the sampling and analysis are complete for each DQO applicable to that tank. Tanks in which characterization has begun but is not complete are designated by being half shaded.		
Corner Triangles	Small triangles near a tank circle give further information on half-shaded tanks. Upper left corner triangles indicate that vapor samples have been taken from the tank. Lower left-hand corner triangles indicate that the tank has been sampled, analyzed, and a formal report has been written on the condensed phase sampling. Further status of the tank will be determined after review of the report is complete. Lower right-hand corner triangles indicate that some review has been completed and it has been determined that more sampling is needed to resolve the DQO requirements. Absence of triangles from a half shaded tank indicates recent condensed phase sampling.		

DISTRIBUTION

Number of copies

OFFSITE - USA

3 Congress of the United States

House of Representatives 1111 Longworth Building Washington D.C. 20515-3703

Ron Wyden, Member of Congress, 3rd District

House of Representatives 1431 Longworth House Office Building

Washington D. C. 20515

Richard "Doc" Hastings, Member of Congress, 4th District

House of Representatives 1229 Longworth House Office Building Washington D. C. 20515

Doug Riggs, c/o Representative Doc Hastings

8 U. S. Department of Energy-Headquarters

1000 Independence Avenue, SW Washington, D. C. 20585

H. Calley EM-362 TREV II
Sherry Gibson EM-55 TREV II
Kenneth Lang EM-36 TREV II
C. O'Dell EM-4 FORS/6E-034

12800 Middlebrook Rd Germantown, MD 20874

Thomas Wright EM-38 TREV II

19901 Germantown Rd Germantown, MD 20874-1290

L. Gunn EM-32 TREV II
C. Majumdar EM-4 Cloverleaf
J. Psaras EM-4 GTN

U. S. DOE-Savannah River Operations Office

P. O Box A, Road 1 Aiken, SC 29802

Bill Spader, DOE SR HLW

1 Argonne National Laboratory 9700 S. Cass Ave Argonne, IL 60439-4837 Dr. George Vandegrift 1 **Ames Laboratory** 105 Spedding Hall Iowa State University Ames, IA 50011 Bill Haas 1 University of Washington Box 354695 Seattle, WA 98195 Rebecca Pixler Library Coordinator, CRESP 1 Confederated Tribes, Umatilla Indian Reservation P. O. Box 638 Pendleton, OR 97801 J. R. Wilkinson, DNR/Hanford Program Manager 1 Defense Nuclear Facilities Safety Board 625 Indiana Ave, N. W., Suite 700 Washington, D. C. 20004 Library 1 Donald Oakley 9612 Hall Road Potomac, MD 20854 1 Fluor Daniel, Inc. 3353 Michelson Drive Irvine, CA 92698 Charles Divona, 512M 1 Foster-Miller, Inc. Power Systems Technology Group 350 Second Avenue Waltham, MA 02154-1196 Maureen Williams 3 National Research Council 2101 Constitution Ave, N.W. Washington D. C. 20418 Robert S. Andrews, Senior Staff Officer, MS HA456

Dr. Greg R. Choppin

l

1404 Potter Ave Richland, WA 99352
Chad Ungerecht

1	Foster Wheeler Environ 3200 George Washington Glen Engel-Cox		
2	Meier Associates, Inc. 8697 Gage Blvd. Kennewick, WA 99336		
	James Bingham Dave Hedengren		
1	ARES Corporation 636 Jadwin Ave., Suite B Richland, WA 99352		
	Lewis Muhlestein		
1	Babad Technical Service 2540 Cordoba Court Richland, WA 99352	<u>s</u>	
1	Los Alamos Technical As 309 Bradley Blvd. Richland, WA 99352	<u>isociates</u>	
	Thuy Tran		
1	Vista Research. Inc. 3000 George Washington V Richland, WA 99352	Way, Suite 2C	
<u>ONSITE</u>	Phil Ohl		
1	SAIC Tracy Friend	H0-50	
1	General Accounting Office C. R. Abraham	e <u>e</u> A1-80	
2	Washington State Depart A. B. Stone Library	ment of Ecology B5-18 B5-18	
1	U. S. Environmental Prot D. R. Sherwood		
23	U. S. Department of Ener J. M. Clark J. J. Davis	gy-Richland Operations Off S7-54 S7-53	<u>ice</u>

S7-54

J. J. Davis J. M. Gray

M. I. Douter	(6)	R1-51
M. L. Dexter	(6)	
R. A. Dodd		S5-07
J. G. Douglas		B4-51
K. C. Douka		S4-43
G. L. Dunford		T4-07
K. A. Elsethager	n	R1-51
T. A. Erickson		R2-50
A. C. Etheridge		H7-07
S. D. Estey		R2-11
W. G. Farley		R1-49
		R2-12
J. G. Field		
K. D. Fowler		R2-11
W. M. Funderbu	ırke	R2-38
G. T. Frater		S7-16
L. A. Gaddis		S3-04
K. A. Gasper		H6-37
J. E. Geary		S6-71
T. C. Geer		R1-43
R. D. Gustavsor	1	R2-50
D. B. Hagmann		H5-61
L. E. Hall		S7-85
B. K. Hampton		S7-40
B. M. Hanlon	(10)	T4-08
G. N. Hanson	(10)	S5-05
W.M. Harty Jr.		S5-13
G. P. Hopkins		S5-03
J. H. Huber		T4-07
S. E. Hulsey		S5-12
M. N. Islam		S5-12
T. D. Jarecki		S7-03
P. Jennings		R2-84
B. A. Johnson		R2-84
G. D. Johnson		S7-14
J. Kalia		R1-43
T. J. Kelley		S7-21
W. J. Kennedy		S7-03
R. A. Kirkbride		H5-27
P. F. Kison		T4-07
N. W. Kirch		R2-11
J. G. Kristofzski		R2-12
M. J. Kupfer		H5-49
M. A. Lane		S8-05
J. A. Lechelt		R2-11
G. T. MacLean		H5-61
R. P. Marshall		H5-61
D. J. McCain	•	R2-12
	t:_	B2-35
M. A. McLaugh	ım	
W. H. Meader		S8-05
L. C. Mercado		T4-08
J. E. Moore		S5-10
K. P. Mortensen	ı	S7-07
A. P. Mousel		S7-12
R. J. Nicklas		S6-72
D. M. Ogden		H0-34
-		
G. L. Parsons		R3-47
M. A. Payne	_	S7-84
L. T. Pedersen,	Jr.	N1-46

HNF-EP-0182-109

R. S. Popielarczyk	R2-38
R. L. Powers	S5-13
T. B. Powers	A3-34
R. E. Raymond (2)	S7-12
W. E. Ross	S5-07
D. J. Saueressig	S8-05
J. S. Schofield	S7-12
R. D. Schreiber	R2-12
E. B. Schwenk, Jr.	B4-51
N. J. Scott-Proctor	S5-01
O. Serrano	R1-43
J. E. Shapley	A2-25
J. P. Shearer	H0-20
D. H. Shuford	S7-01
E. R. Siciliano	H0-31
P. M. Srubek	A0-20
S. M. Stahl	R1-43
J. N. Strode	R2-11
J. L. Stroup	S3-09
R. R. Thompson	R2-12
J. M. Thurman	R1-51
A. M. Umek	S7-8 1
J. E. Van Beek	S2-48
R. J. Van Vleet	A3-34
D. T. Vladimiroff	S8-05
J. A. Voogd	H5-03
K. A. White	S5-09
J. H. Wicks	R2-50
A. E. Young (5)	R1-08
RL Docket File (2)	B1-17
200 West Shift Office	T4-00
200 East Shift Office	S5-04
Central Files	A3-88
Health Physics	S8-05
Environmental	
Data Mgmt Center (2)	H6-08
Solid Waste Data	m
Proc. Center	T4-03
Unified Dose Assessment	
Center (UDAC)	A0-20
Document Proc. Center	A3-94

C. C. Haass	S7-51
R. L. Higgins	S7-54
R. D. Hildebrand	H0-12
D. Irby	S7-54
J. E. Kinzer	S7-50
A. G. Krasopoulos	A4-81
P. E. LaMont	S7-53
J. K. McClusky	S7-54
S. H. Pfaff	S7-54
G. M. Ramin	B4-55
M. J. Royack	S7-54
G. H. Sanders	A5-15
T. R. Sheridan	A4-70
A. B. Sidpara	S7-54
J. M. Silko	S7-54
W. J. Taylor	K6-51
K. G. Wade	S7-54
D. J. Williams	S7-41
D. D. Wodrich	S7-50
Reading Room	H2-53

14 Pacific Northwest Laboratories

P. R. Bredt	P7-25
S. A. Bryan	P7-25
J. B. Colson	K5-25
R. E. Gephart	K9-76
J. K. Hays	K3-70
J. L. Huckaby	K6-80
V. L. Hunter	K7-97
C. M. King	P7-25
A. F. Noonan	K9-91
B. E. Opitz	K6-75
R. D. Scheele	P7-25
R. D. Stenner	K3-54
P. D. Whitney	K5-12
K. D. Wiemers	K6-51

133 Fluor Daniel, Inc., and Affiliated Companies

D. G. Baide	S5- 05
J. J. Badden	T4-07
J. M. Barnett	T4-08
D. A. Barnes	R1-80
D. B. Bechtold	T6-09
L. Bedford	R2-84
J. F. Bertsch	B1-42
M. V. Berriochoa	B3-3 0
H. L. Boston	G3-21
V. C. Boyles	R2-11
K. G. Carothers	R1-56
R. J. Cash	S7-14
J. C. Conner	A2-25
W. L. Cowley	R1-49
S. A. Davis	R2-83
D. K. DeFord	\$8-05
M. P. Delozier	S7-84

Professor of Chemistry Florida State University Department of Chemistry, B-164 Tallahassee, FL 32306

1 Government Accountability Project

West Coast Office 1402 Third Avenue, Suite 1215 Seattle, WA 98101

Thomas E. Carpenter, Director

Heart of America Northwest

1305 Fourth Avenue Cobb Building Suite 208 Seattle, WA 98101

Gerald M. Pollet, Executive Director

1 MACTEC

189 Lafayette Drive, Suite C Oak Ridge, TN 37830

K. S. Redus

Harry Harmon 20 Midlothian Ct. E. Aiken, SC 29803

1 LE.E.R.

6935 Laurel Ave

Takoma Park, MD 20912

Marc Fioravanti

1 I&C Northwest

10109 Orchard Yakima, WA 98908

T. A. Douka

l ENRAF. Inc.

500 Century Plaza Drive, Suite 120 Houston, TX 77073

Donald T. Mears

TRI-CITIES:

TRW Environmental Systems

507 Knight St Richland, WA 99352

Mike Leonard

1 Ogden Environmental & Energy Services

2 <u>U. S. Nuclear Regulatory Commission</u>

Division of Fuel Cycle, Safeguards & Security Mail Stop T8-A33 Washington, DC 20555

Robert Pierson, Chief Dr. Santiago A. Parra

3 Washington State Department of Ecology

Nuclear & Mixed Waste Management Program P.O. Box 47600

Olympia, WA 98504-7600

Scott McKinney R. Stanley Library

1 Oregon State Department of Energy

625 Marion St. NE Salem, OR 97310

Dirk Dunning

1 Oak Ridge National Laboratory

P. O. Box 2008 Oak Ridge, TN 37831-6180

C. Forsberg

MS-6180

Los Alamos National Laboratory

P. O. Box 1663 Los Alamos, NM 87545

Stephen Agnew Group INC-14, J-586

2 Brookhaven National Laboratory

P. O. Box 5000 Upton, NY 11973

Walter Grossman, Bldg 475-C

P. O. Box 509 Upton, NY 11973

K. K. Bandyopadhyay

Sandia National Laboratories

1515 Eubank, NE P. O. Box 5800 Albuquerque, NM 87185

Scott Slezak, Organization 2161, MS 0952

This page intentionally left blank




TABLE I-4. SINGLE-SHELL TANKS STABILIZATION STATUS SUMMARY April 30, 1997

Partial Interim Isolated (PI)	Intrusion Prevent	ion Completed (IP)	Interim Stabi	lized (IS)
EAST AREA	EAST AREA	WEST AREA	EAST AREA	WEST AREA
A-101	A-103	S-104	₅ . A-102	S-104
A-102	≩ A-104	S-105	- A-103	S-105
	A-105		A-104	S-108
AX-101	A-106	SX-107	A-105	S-110
		SX-108	A-106	
BY-102	 AX-102	SX-109		SX-107
BY-103	AX-103	SX-110	AX-102	SX-108
BY-105	AX-104	SX-111	AX-103	SX-109
BY-106		SX-112	AX-104	SX-110
BY-109	B-FARM - 16 tanks	SX-113		SX-111
	BX-FARM - 12 tanks	SX-114	B-FARM - 16 tanks	SX-112
C-103		SX-115	BX-FARM - 12 tanks	SX-113
C-105	BY-101			SX-114
C-106	₿BY-104	T-102	BY-101	SX-115
East Area 11	BY-107	T-103	BY-102	
	BY-108	T-105	BY-104	T-101
WEST AREA	BY-110	T-106	BY-107	T-102
S-101	BY-111	T-108	BY-108	T-103
S-102	BY-112	T-109	BY-110	T-105
S-103	•	T-112	BY-111	T-106
S-105	C-101	T-201	BY-112	T-107
S-106	C-102	T-202		T-108
S-107	C-104	T-203	C-101	T-109
S-108	C-107	T-204	C-102	T-111
S-109	C-108		C-104	T-112
S-110	C-109	TX-FARM - 18 tanks	C-105	T-201
S-111	C-110		C-107	T-202
S-112	C-111	TY-FARM - 6 tanks	C-108	T-203
	C-112		C-109	T-204
SX-101	C-201	U-101	C-110	
SX-102	C-202	U-104	C-111	TX-FARM - 18 tanks
SX-103	C-203	U-112	C-112	
SX-104	C-204	U-102	C-202	TY-FARM - 6 tanks
SX-105	East Area 55	U-202	C-202	
SX-106		Ű-203	C-203	U-101
		U-204	C-204	U-104
T-101		West Area 53	East Area 58	U-110
T-104		Total 108	į.	U-112
T-107				U-201
T-110				U-202
T-111			₹	U-203
			<u>.</u>	U-204
U-102	ž		Ž.	West Area 59
U-103				Total 117
U-105				
U-106				
U-107			k K	
U-108			Controlled, Clean,	and Stable (CCS)
U-109				(550)
U-110			EAST AREA	WEST AREA
	p.		BX-FARM - 12 Tanks	TX-FARM - 18 tanks
U-111			MOVIL WILLIAM - IT I GILLY	V-L WKIM - 19 19USE
U-111 West Area 30		:	DATAMINI - 12 Fallins	TY FARM - 6 tanks

TABLE I-2. TRI-PARTY AGREEMENT SINGLE-SHELL TANK INTERIM STABILIZATION SCHEDULE

April 30, 1997

As part of the Controlled, Clean, and Stable mission, the Single-Shell Tank Interim Stabilization Project goal is to mitigate the risk to the environment from a leak release from aging SSTs, by removing as much of the drainable liquid as practical, for safe storage prior to full waste retrieval.

New TPA milestones were negotiated effective October 1, 1996, to allow greater flexibility in the sequencing of tanks, in light of the latest technical information regarding tank waste safety status and watch list concerns.

Milestone	Description	Due Date	Actual Date	Comments
M-41-20	Start Interim Stabilization of 4 Single-Shell Tanks	9/30/96	3/24/96	S-108, S-110, T-104, and T-107 started.
M-41-21	Start Interim Stabilization of 2 Single-Shell Tanks	5/31/97 (1)		BY-109 started 9/10/96
M-41-22	Start Interim Stabilization of 6 Single-Shell Tanks	9/30/97		Scheduled: A-101, AX-101, BY-103, S-109, SX-103, SX-104
M-41-23	Start Interim Stabilization of 8 Single-Shell Tanks	3/31/98		Tanks to be determined.
M-41-24	Start Interim Stabilization of 9 Single-Shell Tanks	9/30/98		Tanks to be determined.
M-41-25	Start Interim Stabilization of 3 Single-Shell Tanks	3/31/99		Tanks to be determined.
M-41-26	Start Interim Stabilization of 2 Single-Shell Tanks	9/30/99		Tanks to be determined.
M-41-27	Complete Saltwell Pumping of Single-Shell Tanks	9/30/00		

⁽¹⁾ On March 13, DOE signed Change Order Form M1-96-03, extending M-41-21 from March 31 to May 31, 1997.

HNF-EP-0182-109

TABLE I-1. SINGLE-SHELL TANKS INTERIM STABILIZATION STATUS (Sheet 1 of 2)
April 30, 1997

		Interim	Τ	***			Interim	1	***]	Interim	
Tank	Tank	Stabil.	Stabil.		Tank	Tank	Stabil.	Stabil.		Tank	Tank		Combil
		_										Stabil.	Stabil
Number A-101	<u>Integrity</u> SOUND	<u>Date (1)</u> N/A	Method		Number C-101	Integrity ASMD LKR	<u>Date (1)</u> 11/83	Method AR		Number T-108	Integrity ASMD LKR	<u>Date (1)</u> 11/78	Method AR
A-102	SOUND	08/89	SN	***	C-102	SOUND	09/95	JET		T-109	ASMD LKR	12/84	AR
A-103	ASMD LKR	06/88	AR	***	C-103	SOUND	N/A			T-110	SOUND	N/A	
A-104	ASMD LKR	09/78	AR	***	C-104	SOUND	09/89	SN		T-111	ASMD LKR	02/95	JET
A-105	ASMD LKR	07/79	AR	*	C-105	SOUND	10/95	AR (5)	***	T-112	SOUND	03/81	AR(2)(3)
A-106	SOUND	08/82	AR	*	C-106	SOUND	N/A			T-201	SOUND	04/81	AR (3)
AX-101	SOUND	N/A			C-107	SOUND	09/85	JET	***	T-202	SOUND	08/81	AR
AX-102	ASMD LKR	09/88	SN	*	C-108	SOUND	03/84	AR	*	T-203	SOUND	04/81	AR
AX-103	SOUND	08/87	AR		C-109	SOUND	11/83	AR		T-204	SOUND	08/81	AR
AX-104	ASMD LKR	08/81	AR	***	C-110	ASMD LKR	05/95	JET		TX-101	SOUND	02/84	AR
B-101	ASMD IKR	03/81	SN	***	C-111	ASMD LKR	03/84	SN	***	TX-102	SOUND	04/83	JET
B-102	SOUND	08/85	SN	8	C-112	SOUND	09/90	AR		TX-103	SOUND	08/83	JET
B-103	ASMD IKR	02/85	SN	8	C-201	ASMD LKR	03/82	AR		TX-104	SOUND	09/79	SN
8-104	SOUND	06/85	SN	*	C-202	ASMD LKR	08/81	AR	88	TX-105	ASMD LKR	04/83	JET
B-105	ASMD IKR	12/84	AR	₩	C-203	ASMD LKR	03/82	AR		TX-106	SOUND	06/83	JET
B-106	SOUND	03/85	SN		C-204	ASMD LKR	09/82	AR		TX-107	ASMD LKR	10/79	AR
B-107	ASMD LKR	03/86	SN	*	S-101	SOUND	N/A	ļ		TX-108	SOUND	03/83	JET
B-108	SOUND	05/85	SN		S-102	SOUND	N/A			TX-109	SOUND	04/83	JET
B-109	SOUND	04/85	SN		S-103	SOUND	N/A			TX-110	ASMD LKR	04/83	JET
B-110	ASMD LKR	12/84	AR	XX	S-104	ASMD LKR	12/84	AR		TX-111	SOUND	04/83	JET
B-111	ASMD LKR	06/85	SN		S-105	SOUND	09/88	JET		TX-112	SOUND	04/83	JET
B-112	ASMD LKR	05/85	SN	886.	S-106	SOUND	N/A		80	TX-113	ASMD LKR	04/83	JET
8-201	ASMD LKR	08/81	AR (3)	***	S-107	SOUND	N/A		***	TX-114	ASMD LKR	04/83	JET
B-202	SOUND	05/85	AR		S-108	SOUND	12/96	JET (7)		TX-115	ASMD LKR	09/83	JET
B-203	ASMD LKR	06/84	AR	888	S-109	SOUND	N/A			TX-116	ASMD LKR	04/83	JET
B-204	ASMD LKR	06/84	AR	8800 2000	S-110	SOUND	01/97	JET (B)	883	TX-117	ASMD LKR	03/83	JET
BX-101 BX-102	ASMD LKR	09/78	AR	₩ ₩	S-111	SOUND	N/A			TX-118	SOUND	04/83	JET
BX-102	ASMD LKR SOUND	11/78 11/83	AR AR(2)	333 388	S-112 SX-101	SOUND	N/A		888 884	TY-101	ASMD LKR	04/83	JET
BX-103	SOUND	09/89	AR(2) SN	88. 888	SX-101	SOUND	N/A N/A		280.0 280.0	TY-102	SOUND	09/79	AR
BX-105	SOUND	03/81	SN	888 888	SX-102	SOUND	N/A		88600 88600	TY-103 TY-104	ASMD LKR	02/83	JET
BX-106	SOUND	07/95	SN	 	SX-104	ASMD LKR	N/A		### ###	TY-105	ASMD LKR	11/83 02/83	AR JET
BX-107	SOUND	09/90	JET	2000 2000	SX-105	SOUND	N/A		9800 9800	TY-106	ASMO LKR	11/78	
BX-108	ASMD LKR	07/79	SN		SX-106	SOUND	N/A		88 00	U-101	ASMD LKR	09/79	AR AR
BX-109	SOUND	09/90	JET	000 800	SX-107	ASMD LKR	10/79	AR	880 880	U-102	SOUND	N/A	An
BX-110	ASMD LKR	08/85	SN (4)	388 388	SX-108	ASMD LKR	08/79	AR	8883 8883	U-103	SOUND	N/A	
BX-111	ASMD LKR	03/95	JET	2000 2000 2000	SX-109	ASMD LKR	05/81	AR	***** *****	U-104	ASMD LKR	10/78	AR
BX-112	SOUND	09/90	JET	×	SX-110	ASMD LKR	08/79	AR	**************************************	U-105	SOUND	N/A	- CII
BY-101	SOUND	05/84	JET		SX-111	ASMD LKR	07/79	SN	****	U-106	SOUND	N/A	
BY-102	SOUND	04/95	JET	Š	SX-112	ASMD LKR	07/79	AR		U-107	SOUND	N/A	
BY-103	ASMD LKR	N/A		*	SX-113	ASMD LKR	11/78	AR	~	U-10B	SOUND	N/A	
BY-104	SOUND	01/85	JET		SX-114	ASMD LKR	07/79	AR		U-109	SOUND	N/A	
BY-105	ASMD LKR	N/A			SX-115	ASMD LKR	09/78	AŘ	*	U-110	ASMD LKR	12/84	AR
BY-106	ASMD LKR	N/A		*	T-101	ASMD LKR	04/93	SN	*	U-111	SOUND	N/A	
BY-107	ASMD LKR	07/79	JET		T-102	SOUND	03/.81	AR(2)(3)	***	U-112	ASMD LKR	09/79	AR
BY-108	ASMD LKR	02/85	JET	**	T-103	ASMD LKR	11/83	AR		U-201	SOUND	08/79	AR
BY-109	SOUND	N/A			T-104	SOUND	N/A		*	U-202	SOUND	08/79	SN
BY-110	SOUND	01/85	JET		T-105	SOUND	06/87	AR		U-203	SOUND	08/79	AR
BY-111	SOUND	01/85	JET	*	T-106	ASMD LKR	08/81	AR	***	U-204	SOUND	08/79	SN
BY-112	SOUND	06/84	JET		T-107	ASMD LKR	05/96	JET					
LEGEND:													
AR = A	Administrativel	y interim st	abilized							Interim St	abilized Tank	s	117
JET =	Saltwell jet pu	mped to ren	nove drair	ab	le intersti	tial liquid				Not Yet In	nterim Stabili	zed	32
SN = S	Supernate pum	ped (Non-Je	et pumped)									
N/A =	Not yet interim	stabilized			•	Total Single-Shell Tanks 149							
ASMD I	LKR = Assum	ed Leaker											

TABLE H-1. SINGLE-SHELL TANK LEAK VOLUME ESTIMATES (Sheet 3 of 3)

- (q) WHC-1990b, A History of the 200 Area Tank Farms, WHC-MR-0132, Westinghouse Hanford Company, Richland, Washington.
- (r) WHC, 1993, Occurrence Report, Single-Shell Underground Waste Storage Tank 241-BX-111 Surface Level Decrease and Change From Steady State Condition, RL-WHC-TANKFARM-1993-0035, Westinghouse Hanford Company, Richland, Washington.
- (s) WHC, 1993a, Assessment of Unsaturated Zone Radionuclide Contamination Around Single-Shell Tanks 241-C-105 and 241-C-106, WHC-SD-EN-TI-185, REV OA, Westinghouse Hanford Company, Richland, Washington.
- (t) WHC, 1994, Occurrence Report, Apparent Liquid Level Decrease in Single Shell Underground Storage Tank 241-T-111; Declared an Assumed Re-Leaker, RL-WHC-TANKFARM-1994-0009, Westinghouse Hanford Company, Richland, Washington.

HNF-EP-0182-109

TABLE H-1. SINGLE-SHELL TANK LEAK VOLUME ESTIMATES (Sheet 1 of 2) April 30, 1997

		Арги	30, 1997					
	Date Declared		Associated	Interim				
	Confirmed or	Volume	KiloCuries	Stabilized	Leak Estimate			
Tank No.	Assumed Leaker	(Gallons)	<u>137.cs</u>	<u>Date</u>	Undated	Reference		
241-A-103	1987	5500	•	06/88	1987	(j)		
241-A-104	1975	500 to 2500	0.8 to 1.8 (q)	09/78	1983	(a) (q)		
241-A-105	1963	10000 to	85 to 760 (b)	07/79	1991	(b),(c)		
244 437 422		277000						
241-AX-102 241-AX-104	1988 1 97 7	3000		09/88	1989	(h)		
241-B-101	1974			08/81	1989	(g)		
241-B-103	1978			03/81 02/85	1989 1989	(g) (g)		
241-B-105	1978			12/84	1989	(g)		
241-B-107	1980	8000		03/85	1986	(d),(f)		
241-B-110	1981	10000		03/85	1986	(d)		
241-B-111 241-B-112	1978 1978	2000		06/85 05/85	1989	(g)		
241-B-201	1980	1200	•	08/81	1989 1984	(g) (e),(f)		
241-B-203	1983	300		06/84	1986	(d)		
241-B-204	1984	400		06/84	1989	(g)		
241-BX-101	1972			09/78	1989	(g)		
241-BX-102 241-BX-108	1971 1974	70000 2500	50 (I)	11/78	1986	(d)		
241-BX-108 241-BX-110	1974	2500	0.5 (i)	07/79 08/85	1986 1989	(d)		
241-BX-111	1984	 		03/95	1993	(g) (g),(r)		
241-BY-103	1973	<5000		N/A	1983	(a)		
241-BY-105	1984			N/A	1989	(g)		
241-BY-106	1984			N/A	1989	(g)		
241-BY-107 241-BY-108	1984 1972	15100 <5000		07/79	1989	(g)		
241-C-101	1980			02/85	1983	(a)		
241-C-101 241-C-110	1984	20000 2000		11/83 05/95	1986 1989	(d)		
241-C-111	1968	5500		03/84	1989	(g) (a)		
241-C-201	1988	550		03/82	1987	(g) (i)		
241-C-202	1988	450		08/81	1987	(i)		
241-C-203 241-C-204	1984 1988	400 350		03/82 09/82	1986	(d)		
241-S-104	1968	24000			1987	(i)		
			·····	12/84	1989	(g)		
241-SX-104 241-SX-107	1988 1964	6000 < 5000		N/A	1988	(k)		
241-SX-108	1962	2400 to	17 to 140 (m) (g	10/79 08/79	1983 1991	(a) (m) (q)		
		35000		00,.0	1001	(11) (4)		
241-SX-109	1965	< 10000	<40 (n)	05/81	1992	(n)		
241-SX-110	1976	5500		08/79	1989	(g)		
241-\$X-111 241-\$X-112	1974 1969	500 to 2000 30000	0.6 to 2.4 (I) (q) 40 (I)	07/79 07/79	1986	(d) (g)		
241-SX-113	1962	15000	8 (1)	11/78	1986 1986	(d) (d)		
241-SX-114	1972			07/79	1989	(g)		
241-SX-115	1965	50000	21 (o)	09/78	1992	(0)		
241-T-101	1992	7500		04/93	1992	(p)		
241-T-103 241-T-106	1974 1973	<1000 115000	40 (1)	11/83	1989	(g)		
241-T-106	1973	113000	40 (I)	08/81 05/96	1986 1989	(d)		
241-T-108	1974	<1000		11/78	1980	(g) (f)		
241-T-109	1974	<1000		12/84	1989	(g)		
241-T-111	1979, 1994	<1000		02/95	1994	(f)(t)		
241-TX-105 241-TX-107	1977 1994	2500		04/83	1989	(g)		
241-TX-107 241-TX-110	1984 1977	2500		10/79 04/83	1986 1989	(d)		
241-TX-113	1974			04/83	1989	(g) (g)		
241-TX-114	1974			04/83	1989	(g)		
241-TX-115 241-TX-116	1977 1977			09/83	1989	(g)		
241-TX-116 241-TX-117	1977 1977			04/83 03/83	1989 1989	(g)		
241-TY-101	1973	<1000		04/83		(g)		
241-TY-103	1973	3000	0.7 (1)	04/83	1980 1 986	(f) (d)		
241-TY-104	1981	1400		11/83	1986	(d)		
241-TY-105	1960	35000	4 (1)	02/83	1986	(d)		
241-TY-106	1959	20000	2 (1)	11/78	1986	(d)		
241-U-101 241-U-104	1959 1961	30000	20 (1)	09/79	1986	(d)		
241-U-1104 241-U-110	1961 1975	55000 5000 to 8100	0.09 (I) 0.05 (g)	10/78	1986	(d)		
241-U-112	1980	8500	J.UJ (q)	12/84 09/79	1986 1986	(d) (q) (d)		
67 Tanks		<600,000 - 900,000				14)		
		~000,000 - 300,000						

N/A = not applicable (not yet interim stabilized) Footnotes: See next page

TABLE G-3. WEST AREA INACTIVE MISC. UNDERGROUND STORAGE TANKS AND SPECIAL SURV. FACILITIES
INACTIVE - no longer receiving waste transfers
April 30, 1997

				MONITOREL)
<u> FACILITY</u>	LOCATION	RECEIVED WASTE FROM:	(Gallons)	<u>BY</u> -	REMARKS
216-TY-201	E. of TY Farm	Supernate from T-112	Unknown	NM	Isolated
231-W-151-001	N. of Z Plant	231-Z Floor drains	Unknown	NM	Inactive, last data 1974
231-W-151-002	N. of Z Plant	231-Z Floor drains	Unknown	NM	Inactive, last data 1974
240-S-302	S Farm	240-S-151 DB	8647	CASS/ENRAF	Assumed Leeker EPDA 85-04
241-S-302-A	S Farm	241-S-151 DB	0	CASS/FIC *	Assumed Leaker TF-EFS-90-042
			* FIC in Intrus	sion mode	Partially filled with grout 2/91, determined still assumed leaker after leak test
241-S-302-B	S Farm	S Encasements	Unknown	NM	Isolated 1985 (1)
241-SX-302	SX Farm	SX-151 DB, 151 TB	Unknown	NM	Isolated 1987
241-SX-304	SX Farm	SX-152 Transfer Box, SX-151 DB	Unknown	NM	Isolated 1985 (1)
241-T-301	T Farm	DB T-151, -151, -153, -252	Unknown	NM	Isolated 1985 (241-T-301B)
241-TX-302	TX Farm	TX-153 DB	Unknown	NM	Isolated 1985 (1)
241-TX-302-X-B	TX Farm	TX Encasements	Unknown	NM	Isolated 1985 (1)
241-TX-302-B	TX Farm	TX-155 DB	1600	CASS/MT	New MT installed 7/16/93
241-TX-302B(R)	E. of TX Farm	TX-155 DB	Unknown	NM	Isolated
241-TY-302-A	TY Farm	TX-153 DB	Unknown	NM	Isolated 1985 (1)
241-TY-302-B	TY Farm	TY Encasements	Unknown	NM	Isolated 1985 (1)
241-Z-8	E. of Z Plant	Recuplex waste	Unknown	NM	Isolated, 1974, 1975
242-T-135	T Evaporator	T Evaporator	Unknown	NM	isolated
242-TA-R1	T Evaporator	Z Plant waste	Unknown	NM	Isolated
243-S-TK-1	N. of S Farm	Pers. Decon. Facility	Unknown	NM	isolated
244-U-TK/SMP	U Farm	DCRT - Receives from several farms	Unknown	NM	Not yet in use
244-TXR VAULT	TX Farm	Transfer lines	Unknown	NM	Interim Stabilized, MT removed 1984 (1)
244-TXR-TK/SMP-001	TX Farm	Transfer lines	Unknown	NM	Interim Stabilized, MT removed 1984 (1)
244-TXR-TK/SMP-002	TX Farm	Transfer lines	Unknown	NM	Interim Stabilized, MT removed 1984 (1)
244-TXR-TK/SMP-003	TX Farm	Transfer lines	Unknown	NM	Interim Stabilized, MT removed 1984 (1)
270-W	SE of U Plant	Condensate from U-221	Unknown	NM	isolated 1970
361-T-TANK	T Plant	Drainage from T-Plant	Unknown	NM	isolated 1985 (1)
361-U-TANK	บ Plant	Drainage from U-Plant	Unknown	NM	Interim Stabilzed, MT removed 1984 (1)

est Area inactive facilities 2	

LEGEND: DB - Diversion Box, TB - Transfer Box
DCRT - Double-Contained Receiver Tank
TK - Tank
SMP - Sump
R - Usually denotes replacement
FIC - Surface Level Monitoring Device
MT - Manual Tape
O/S - Out of Service
CASS - Computer Automated Surveillance System
NM - Not Monitored
ENRAF - Surface Level Monitoring Device

NF-EP-0182-109

TABLE G-1. EAST AND WEST AREA MISCELLANEOUS UNDERGROUND STORAGE TANKS AND SPECIAL SURVEILLANCE FACILITIES

ACTIVE - still running transfers through the associated diversion boxes or pipeline encasements
April 30, 1997

<u>FACILITY</u>	<u>LOCATION</u>	PURPOSE (receives waste from:)	(Gallons)	MONITORED BY	<u>REMARKS</u>
EAST AREA					
241-A-302-A	A Farm	A-151 DB	947	SACS/DIP TUBE	Increase from drain off from Diversion Box & WTF to ENRAF
241-ER-311	B Plant	ER-151, ER-152 DB	3600	SACS/CASS/FIC	Increase from drain off from Diversion Box
241-AX-152	AX Farm	AX-152 DB	3444	SACS/MT	DIAL O/S, using MT, pumped Jan. 97, increase from drain off from Diversion Box
241-AZ-151	AZ Farm	AZ-152 DB, AZ Loop Seal	5374	SACS/CASS/FIC	Volume changes daily-rec'd from A-417, 2/13/
241-AZ-154	AZ Farm	AZ-102 Htg coil steam condensate	2	SACS/CASS/MT	Automatic Pump
244-BX-TK/SMP	BX Complex	DCRT - Receivers from several farms	18145	SACS/MANUALLY	Using Manual Tape for tank
244-A-TK/SMP	A Complex	DCRT - Receives from several farms	6235	MCS	WTF
A-350	A Farm	Collects drainage	464	SACS/MT	WTF, pumped Jan. 97
AR-204	AY Farm	RR Cars during transfer to rec. tanks	550	DIP TUBE	Alarms on CASS
A-417	A Farm	A-702 Process condensate	12344	SACS/DIP TUBE	WTF. pumped 4/29/97
CR-003-TK/SUMP	C Farm	DCRT	4105	MT/ZIP CORD	Zip cord in sump O/S 3/11/96
WEST AREA					
241-TX-302-C	TX Farm	TX-154 DB	7733	SACS/CASS/ENRAF	
241-U-301-B	U Farm	U-151, U-152, U-153, U-252 DB	7947	SACS/CASS/ENRAF	Returned to service 12/30/93
241-UX-302-A	U Plant	UX-154 DB	7115	SACS/CASS/ENRAF	
241-5-304	S Farm	S-151 DB	2465	SACS/RS	10/91, replaced S-302-A, Manual FIC
244-S-TK/SMP	S Farm	DCRT - Receives from several farms	7340	SACS/MANUALLY	CWF
244-TX-TK/SMP	TX Farm	DCRT - Receives from several farms	25111	SACS/MANUALLY	MT
Vent Station Catch	Tank	Cross Country Transfer Line	287	SACS/MANUALLY	MT
		Total Active Facilities 18	LEGEND:	DB - Diversion Box	

DCRT - Double-Contained Receiver Tank

FIC - Food Instrument Corporation measurement device

CWF - Weight Factor/SpG = Corrected Weight Factor

CASS - Computer Automated Surveillance System

SACS - Surveillance Automated Control System

MCS - Manitar and Control System

ENRAF - Surface Level Measuring Device

RS - Robert Shaw instrument measurement device

TK · Tank

SMP - Sump

MFIC - Manual FIC

MT - Manual Tape

0/8 - Out of Service

Note: Readings may be taken manually or automatically by FIC (or ENRAF). All FIC/ENRAF are connected to CASS. All tanks on CASS (either auto or manual) are also on the SACS database. If automatic connections to CASS are broken, readings are taken manually. Manual readings include readings taken by manual tape, manual FIC, or manual readings of automatic FIC (If CASS is printing "0"). Readings may also be taken by zip cord, which are acceptable but less accurate.

This page intentionally left blank

TABLE F-2. SUMMARY OF WASTE TRANSACTIONS IN THE DOUBLE-SHELL TANKS

SUMMARY OF WASTE TRANSACTIONS IN THE DOUBLE-SHELL TANK (DST) SYSTEM FOR APRIL 1997: ALL VOLUMES IN KGALS

- There was a net change of +57 Kgals in the DST system for April 1997.
- The total DST inventory as of April 30, 1997 was 18,871 Kgals.
- There was no Saltwell Liquid (SWL) pumped to the East Area DSTs in April.
- There was no Saltwell Liquid (SWL) pumped to Tank 102-SY (West Area DST) in April.
- Evaporator 242-A, Campaign 97-1 completed processing DST waste in early April.
- There was ~21 Kgals Waste Volume Reduction (WVR) of DST waste, via the 242-A Evaporator in April.
- Evaporator Campaign 97-1 summary and process statistics can be found in
- "Campaign 97-1 Post Run Document", issued by 242-A Eyaporator process engineering.
- There was no Hanford Facility generated waste sent to the DSTs in April.

APRIL 1997 DST WASTE RECEIPTS												
FACILITY GENERA	TIONS	OTHER GAINS ASSOCI	ATED WITH	OTHER LOSSES ASSOCI	S ASSOCIATED WITH							
Evap. Flush etc.	70 Kgal (2AW, 6AW)	SLURRY	+0 Kgal	SLURRY	-2 Kgal							
Evap. WVR	-21 Kgals (2AW)	CONDENSATE	+26 Kgal	CONDENSATE	-19 Kgal							
TOTAL	49 Kgal	INSTRUMENTATION	+4 Kgal	INSTRUMENTATION	-0 Kgal							
		UNKNOWN	+1 Kgal	UNKNOWN	-2 Kgal							
		TOTAL	+31 Kgal	TOTAL	-23 Kgal							

	ACTUAL DST WASTE RECEIPTS	PROJECTED D\$T WASTE RECEIPTS	MISC. DST CHANGES (+/-)	WVR	NET DST CHANGE	TOTAL DST VOLUME
OCT96	38	51	+7	0	+45	19093
NOV96	13	42	-21	0	-8	19085
DEC96	10	64	-5	0	+5	19090
JAN97	46	61	-11	0	+35	19125
FEB97	69	148	+2	0	+71	19196
MAR97	36	157	-18	-400	-382	18814
APR97	0	170	8	+49	+57	18871
MAY97	-	194		0		
JUN97		184		0		
JUL97		286		-759		
AUG97		374		0		
SEP97		355		0		

NOTE: The WVR number in March is the ACTUAL WVR; The WVR in July 1997 is projected Waste Volume Reductions through the 242-A Evaporator.

TABLE F-1. PERFORMANCE SUMMARY (Sheet 1 of 2) WASTE VOLUMES (Kgallons) April 30, 1997

INCREASES/DECREASES IN WASTE VOLUMES STORED IN DOUBLE-SHELL TANKS

STORED IN DOUB	PE-SHEL	L I ANKS	
		THIS	FY1997
SOURCE	1	MONTH	TO DATE
B PLANT		0	54
PUREX TOTAL (1)		0	0
PFP (1)		0	0
T PLANT (1)		0	o
S PLANT (1)		0	7
300 AREAS (1)		0	17
400 AREAS (1)		0	0
SULFATE WASTE -100 N (2)		0	0
TRAINING/X-SITE (9)		0	46
TANK FARMS (6)		0	25
SALTWELL LIQUID (8)		0	63
OTHER GAINS		31	152
Slurry increase (3)	0		
Condensate	26		
Instrument change (7)	4		
Unknown (5)	1		
OTHER LOSSES		-23	-190
Slurry decrease (3)	.2		
Evaporation (4)	-19		
Instrument change (7)	0		
Unknown (5)	-2		
EVAPORATED		49	-351
GROUTED		0	0
TOTAL		57	-177

CUMULATIVE EVAPORATION - 1950 TO PRESENT WASTE VOLUME REDUCTION

FACILITY	
242-B EVAPORATOR (10)	7172
242-T EVAPORATOR (1950's) (10)	9181
IN-TANK SOLIDIFICATION UNIT 1 (10)	11876
IN-TANK SOLIDIFICATION UNIT 2 (10)	15295
IN-TANK SOLID. UNIT 1 & 2 (10)	7965
(after conversion of Unit 1 to a cooler for Unit 2)	
242-T (Modified) (10)	24471
242-S EVAPORATOR (10)	41983
242-A EVAPORATOR (11)	73689
242-A Evaporator was restarted April 15, 1994,	
after having been shut down since April 1989.	
Total waste reduction since restart:	8882

Footnotes: See Next Page

This page intentionally left blank.

TABLE E-6. INVENTORY AND STATUS BY TANK - SINGLE-SHELL TANKS

April 30, 1997

FOOTNOTES:

E-14

Total Waste is calculated as the sum of Sludge and Saltcake plus Supernate.

The category "Interim Isolated" (II) was changed to "Intrusion Prevention" (IP) in June 1993. See section C. "Tank and Equipment Code and Status Definitions." Stabilization information from WHC-SD-RE-TI-178 SST STABILIZATION RECORD, latest revision, or SST Stabilization or Cognizent Engineer

(a) BY-109 - Following Information from Cognizant Engineer:

Saltwell pumping resumed April 2, 1997, after temporary suspension due to Flammable Gas issues.

Total waste: 423 Kgal (No change) Supernate: 0 Kgal (No change) Drainable Interstitial Liquid: 24 Kgal Pumped this Month: 3,1 Kgal Total Pumped: 157 Kgal

Drainable Liquid Remaining: 24 Kgal Pumpable Liquid Remaining: 9.4 Kgal

Sludge: 83 Kgel (No change) Saltcake: 340 Kgel (No change)

Note: Drainable Interstitial, Drainable Liquid Remaining, and Pumpable Liquid Remaining estimates were updated based on current diptube readings and latest porosity estimates.

Total waste, sludge, and saltcake estimates will be adjusted at completion of pumping, based on in-tank photographs and final waste surface levels.

(b) T-104 - Following information from Cognizant Engineer:

Pumping started March 24, 1996; the pump failed August 26, and resumed after pump was replaced. Pumping temporarily suspended October 18 for Flammable Gas issues, and resumed pumping on April 17, 1997.

Total waste: 365 Kgal

Supernate: 0 Kgal (No change)
Drainable interstitial Liquid: 38.4 Kgal

Pumped this Month: 3.1 Kgal Total Pumped: 93.7 Kgal

Drainable Liquid Remaining: 38.4 Kgal Pumpable Liquid Remaining: 35.4 Kgal

Sludge: 365 Kgal

Sattcake: O Kgal (No change)

Note: The drop in tank waste volume is approximately 75% of the corresponding liquid volume removed. The waste continues to shift as water is removed from it.

A porosity cannot be determined until the waste stabilizes.

TABLE E-6. INVENTORY AND STATUS BY TANK - SINGLE-SHELL TANKS
April 30, 1997

	TANK STATUS						LIQ	UID VOLU	ME		SOLIDS	VOLUME	VOLUI	VE DETERM	INATION			
				·		DRAIN- ABLE	PUMPED		DRAIN- ABLE	PUMP- ABLE								SEE FOOTNOTE
			STABIL/		SUPER-	INTER-	THIS	TOTAL	LIQUID	FIGUID	ļ	SALT	LIQUIDS	SOLIDS	SOLIDS	LAST	LAST	FOR
T 4 6 11/	WASTE	TANK	ISOLATION		i	STIT.	MONTH	PUMPED	REMAIN	REMAIN	SLUDGE	-	VOLUME	VOLUME	VOLUME	IN-TANK		THESE
TANK	MAT'Ł.	INTEGRITY	STATUS	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	METHOD	METHOD	UPDATE	PHOTO	VIDEO	CHANGES
T-109	NCPLX	ASMD LKR	IS/IP	58	l 0	0	0.0	0.0	•	^	1 50	•	1			l 00/05/00		ı
T-110	NCPLX	SOUND	/PI	379	3				0	0	1	0	M	M	12/30/84			l ,.
T-111	NCPLX	ASMD LKR	IS/PI			39	0.0	0.0	42	60	376	0	, r	FP	04/28/82	1		(c)
T-112	NCPLX	SOUND	IS/PF	446	0 7	34	0.0	9.6	34	29	446	0	,	FP	04/18/94	1	02/13/95	
T-201	NCPLX	SOUND	IS/IP	67	l '	0	0.0	0.0	7	7	60	0	l	FP	04/28/82			
T-201	NCPLX			29	1	3	0.0	0.0	4	0	28	0	M	PS	05/31/78			
		SOUND	IS/IP	21	0	2	0.0	0.0	2	0	21	0	FP	P 	07/12/81	07/06/89		
T-203	NCPLX	SOUND	IS/IP	35	0	4	0.0	0.0	4	0	35	0	М	PS	01/31/78			
T-204	NCPLX	SOUND	IS/IP	38	٥	4	0.0	0.0	4	0	38	0	FP	P	07/22/81	08/03/89		
16 SIN	GLE-SHELL	TANKS	TOTALS:	1935	31	185	3.1	139,6	216	173	1904	0						
									· · -									•
								TX TA	NK FARM	STATUS								
	I NCPLX	SOUND	IS/IP/CCS	87	3	2	0.0	0.0	5	0	84	0	F	P	02/02/84	10/24/85		ł
TX-10	NCPLX	SOUND	IS/IP/CCS	217	0	22	0.0	94.4	22	0	.0	217	М	S	08/31/84	10/31/85		l
	3 NCPLX	SOUND	IS/IP/CCS	157	0	15	0.0	68.3	15	0	157	0	F	S	08/14/80	10/31/85		1
TX-10-	NCPLX	SOUND	IS/IP/CCS	65	1	14	0.0	3.6	15	0	0	64	F	₽P	04/06/84	10/16/84		1
TX-10!	5 NCPLX	ASMD LKR	IS/IP/CCS	609	0	20	0.0	121.5	20	0	0	609	М	PS	08/22/77	10/24/89		
TX-10	NCPLX	SOUND	IS/IP/CCS	453	0	10	0.0	134.6	10	0	0	453	M	s	08/29/77	10/31/85		
TX-10	7 NCPLX	ASMD LKR	IS/IP/CCS	36	1	1	0.0	0.0	2	0	0	35	FP	FP	01/20/84	10/31/85		1
TX-10	NCPLX	SOUND	IS/IP/CCS	134	0	0	0.0	13,7	0	0	0	134	P	FP	05/30/83	09/12/89		
TX-10	NCPLX	SOUND	IS/IP/CCS	384	0	10	0.0	72.3	10	0	0	384	F	PS	05/30/83	10/24/89		
TX-110	NCPLX	ASMD LKR	IS/IP/CCS	462	0	15	0.0	115.1	15	0	0	462	м	PS	05/30/83	10/24/89		
TX-11	NCPLX	SOUND	IS/IP/CCS	370	0	9	0.0	98.4	9	0	0	370	м	PS	07/26/77	09/12/89		
TX-11	NCPLX	SOUND	IS/IP/CCS	649	0	24	0.0	94.0	24	0	0	649	P	PS	05/30/83			1
TX-11:	NCPLX	ASMD LKR	IS/IP/CCS	607	0	16	0.0	19.2	16	0	0	607	м	PS	05/30/83		09/23/94	
TX-114	NCPLX	ASMD LKR	IS/IP/CCS	535	0	15	0.0	104.3	15	o	٥	535	М м	PS	05/30/83	04/11/83		1
TX-115	NCPLX	ASMD LKR	IS/IP/CCS	640	0	19	0.0	99.1	19	0	٥	640	M	s	03/25/83	06/15/88	-2,,,,,	
TX-116	NCPLX	ASMD LKR	IS/IP/CCS	631	٥	23	0.0	23.8	23	o	ő	631	M	PS	03/23/03	10/17/89		
	NCPLX	ASMD LKR	IS/IP/CCS	626	٥	8	0.0	54.3	8	0	ľő	626	M	PS PS	12/31/71	04/11/83		
	NCPLX	SOUND	IS/IP/CCS	347	o	27	0.0	89.1	27	0	0	347	F F	, rs	11/17/80	12/19/79		
						,					<u> </u>							<u> </u>
8 SIN	GLE-SHELL	TANKS	TOTALS:	7009	5	250	0.0	1205.7	255	0	241	6763						

₹12

TABLE E-6. INVENTORY AND STATUS BY TANK - SINGLE-SHELL TANKS
April 30, 1997

	TANK S	STATUS					LIO	UID VOLU	ME		SOLIDS	VOLUME		VOLUM	E DETERMIN	NATION	· ·	
						DRAIN-			DRAIN-	PUMP-								SEE
					ļ	ABLE	PUMPED		ABLE	ABLE								FOOTNOTES
			STABIL/	TOTAL	SUPER-	INTER-	THIS	TOTAL	LIQUID	LIQUID	į	SALT	LIQUIDS	SOLIDS	SOLIDS	LAST	LAST	FOR
	WASTE	TANK	ISOLATION	WASTE	NATE	STIT.	MONTH	PUMPED	REMAIN	REMAIN	SLUDGE	CAKE	VOLUME	VOLUME	VOLUME	IN-TANK	IN-TANK	THESE
ANK	MAT'L.	INTEGRITY	STATUS	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	METHOD	METHOD	UPDATE	PHOTO	VIDEO	CHANGES
								C TA	NK FARM	STATUS								
-101	NCPLX	ASMD LKR	IS/IP	88	0	3	0.0	0.0	3	0	88	0	м	M	11/29/83	11/17/87		
102	DC	SOUND	IS/IP	316	0	30	0.0	46.7	30	17	316	0	F	FP	09/30/95	05/18/76	08/24/95	;
103	NCPLX	SOUND	/PI	195	133	0	0.0	0.0	133	133	62	0	F	s	10/20/90	07/28/87		(c)
-104	CC	SOUND	IS/IP	295	0	11	0.0	0.0	11	5	295	0	FP	₽	09/22/89	07/25/90		į.
-105	NCPLX	SOUND	IS/PI	134	2	30	0.0	0.0	32	9	132	0	F	s	10/31/95	08/05/94	08/30/95	;[
-106	NCPLX	SOUND	/PI	229	32	16	0.0	0.0	48	52	197	0	F	PS	04/28/82	08/05/94	08/08/94	(c)
-107	DC	SOUND	IS/IP	237	0	24	0.0	40.8	24	15	237	0	F	S	09/30/95	00/00/00		1
-108	NCPLX	SOUND	IS/IP	66	0	0	0.0	0.0	0	0	66	0	М	s	02/24/84	12/05/74	11/17/94	
-109	NCPLX	SOUND	IS/łP	66	4	0	0.0	0.0	4	0	62	0	М	PS	11/29/83	01/30/76		1
C-110	DC	ASMD LKR	IS/IP	178	1	28	0.0	15.5	29	15	177	0	F	FMP	06/14/95	08/12/86	05/23/95	;
-111	NCPLX	ASMD LKR	IS/IP	57	0	0	0.0	0.0	0	0	57	0	м	s	04/28/82	02/25/70	02/02/95	:[
-112	NCPLX	SOUND	IS/IP	104	0	32	0.0	0.0	32	26	104	0	м	PS	09/18/90	09/18/90		
-201	NCPLX	ASMD LKA	IS/IP	2	0	0	0.0	0.0	0	0	2	0	P	MP	03/31/82	12/02/86		1
-202	EMPTY	ASMD LKR	IS/IP	1	0	0	0.0	0.0	0	0	1	0	P	М	01/19/79	12/09/86		
-203	NCPLX	ASMD LKR	IS/IP	5	0	0	0.0	0.0	0	0	5	0	Р	MP	04/28/82	12/09/86		1
C-204	NCPLX	ASMD LKR	IS/IP	3	0	0	0.0	0.0	0	0	3	0	P	MP	04/28/82	12/09/86		-
6 SINO	GLE-SHELL	TANKS	TOTALS:	1976	172	174	0.0	103,0	346	272	1804		 					ļ
0 01111	Jee officee	171110	TOTALS.	1970	1/2	174	0.0	103.0	340	2/2	1804		<u> </u>			<u> </u>		1
S-101	NCPLX	SOUND	/PI	407	١	0.4			NK FARM							·		ı
-101	DSSF	SOUND	/PI	427 549	12 0	84	0.0	0.0	96	127	244	171	F	PS	09/16/80			(c)
-103	DSSF	SOUND	-		_	230	0.0	0.0	230	239	4	545	P	FΡ	04/28/82			(c)
-103	NCPLX	ASMD LKR	/PI IS/IP	248 294	17 1	85	0.0	0.0	102	97	10	221	M	\$	11/20/80			(c)
-105	NCPLX	SOUND	IS/IP		_	28	0.0	0.0	29	23	293	0	M	M	12/20/B4	12/12/84		
-106	NCPLX	SOUND	/PI	456	0	35	0.0	114.3	35	13	2	454	MP	s 	09/26/88			
-107	NCPLX	SOUND		479	4	186	0.0	97.0	190	168	28	447	P	FP 	12/31/93		09/12/94	1
-108	NCPLX	SOUND	/PI IS/PI	37 6	14	45	0.0	0.0	59	88	293	69	F	P\$	09/25/80			(c)
-109	NCPLX	SOUND		450	0	4	0,0	199.8	4	0	4	446	P	MP	12/20/96		12/03/96	·
-110	NCPLX	SOUND	/PI	568	0	141	0.0	111.0	141	119	13	555	F	P\$	09/30/75	08/24/84		1
-110 -111	NCPLX	SOUND	IS/PI	390	0	30	0.0	203.1	30	23	131	259	F	PS	05/14/92	· ·	12/11/96	Ì
-111 -112	NCPLX	SOUND	/Pl /Pl	596	10	195	0.0	3.3	205	134	139	447	P	FP 	04/28/82	08/10/89		
	HOLEX	300110	/FI	523	0	110	0.0	1 25.1	110	107	5	518	P	FP	12/31/93	03/24/87		
											•		1					

1

TABLE E-6. INVENTORY AND STATUS BY TANK - SINGLE-SHELL TANKS
April 30, 1997

	TANK S	STATUS					LIO	UID VOLU			SOLIDS	VOLUME	VOLUM	E DETERMI	NOTAN	PHOTOS/	VIDEOS	
						DRAIN-			DRAIN-	PUMP-								SEE
					SUPER-	ABLE	PUMPED		ABLE	ABLE								FOOTNOTE
			STABIL/		NATE	INTER-	THIS	TOTAL	LIQUID	LIQUID	ŀ	SALT	LIQUIDS	SOLIDS	SOLIDS	LAST	LAST	FOR
TANK	WASTE MAT'L.	TANK	ISOLATION		LIQUID	STIT.	MONTH	PUMPED	REMAIN		SLUDGE		VOLUME	VOLUME	VOLUME	IN-TANK	IN-TANK	THESE
IANK	MAI L.	INTEGRITY	STATUS	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	METHOD	METHOD	UPDATE	РНОТО	VIDEO	CHANGES
								A TAI	NK FARM	STATUS								
A-101	DSSF	SOUND	/PI	953	0	413	0.0	0.0	413	441	j 3	950	P	F	11/21/80	08/21/85		(c)
-102	DSSF	SOUND	IS/Pt	41	4	2	0.0	39.5	6	0	15	22	Р	FP	07/27/89	07/20/89		
A-103	DSSF	ASMD LKR	IS/IP	371	5	15	0.0	111.0	20	0	366	0		FP	06/03/88	12/28/88		
A-104	NCPLX	ASMD LKR	IS/IP	. 28	0	0	0.0	0.0	0	0	28	0	м	PS	01/27/78	06/25/86		ŀ
A-105	NCPLX	ASMD LKR	IS/IP	19	0	4	0.0	0.0	4	0	19	0	P	MP	08/23/79	08/20/86		
A-106	CP	SOUND	IS/IP	1 25	0	7	0.0	0.0	7	0	125	,0	Р	M	09/07/82	08/19/86		
6 SING	LE-SHELL	TANKS	TOTALS	1537	9	441	0.0	150.5	450	441	556	972	-					
	•••							AV 50.1		- CIED A STATE	·							
X-10	1 DSSF	SOUND	/PI	748	l 0	320	0.0		NK FARM			745	1 .	-	05/00/00			
4X-10		ASMD LKR	IS/IP	39] 3	14		0.0	320	338	3 7	745	P	F	05/06/82	08/18/87		(c)
X-10		SOUND	IS/iP	112		36	0.0 0.0	13.0 0.0	17	3	1	29	F	s	09/06/88	06/05/89		
	4 NCPLX	ASMD LKR	IS/IP	7	ő	0	0.0	0.0	36 0	3 0	7	110	l r P	S	08/19/87	08/13/87		
	· NOI EX	HOURD EAN		,	ľ	U	0.0	0.0	U	U	′	0		М	04/26/82	08/18/87		İ
4 SING	LE-SHELL 1	TANKS	TOTALS:	906	3	370	0.0	13.0	373	344	19	684						
								R TAN	K FARM	PITATE								
B-101	NCPLX	ASMD LKR	IS/IP	113	0	6	0.0	0.0	6	0	113	o	P	F	04/28/82	05/19/83		l
B-102	NCPLX	SOUND	IS/IP	32	4	0	0.0	0.0	4	o	18	10	Р	F	08/22/85	08/22/85		ŀ
3-103	NCPLX	ASMD LKR	IS/IP	59	0	0	0.0	0.0	0	0	59	0	F	F	02/28/85	10/13/88		ŀ
3-104	NCPLX	SOUND	IS/IP	371	1	46	0.0	0.0	47	40	301	69	ĺм	М	06/30/85	10/13/88		[
3-105	NCPLX	ASMD LKR	IS/IP	306	0	23	0.0	0.0	23	0	40	266	P	MP	12/27/84	05/19/88		ŀ
3-106	NCPLX	SOUND	IS/IP	117	1 1	6	0.0	0.0	7	0	116	0	F	F.	03/31/85	02/28/85		
3-107	NCPLX	ASMD LKR	IS/IP	165	1	12	0.0	0.0	13	7	164	0	м	M	03/31/85	02/28/85		<u> </u>
3-108	NCPLX	SOUND	IS/IP	94	0	4	0.0	0.0	4	0	94	0	F	F	05/31/85	05/10/85		
3-109	NCPLX	SOUND	IS/IP	127	0	8	0.0	0.0	8	0	127	0	м	M	04/08/85	04/02/85		
3-110	NCPLX	ASMD LKR	IS/IP	246	1	22	0.0	0.0	23	17	245	0	MP	MP	02/28/85	03/17/88		ĺ
-111	NCPLX	ASMD LKR	IS/IP	237	1	21	0.0	0.0	22	16	236	0	F	F	06/28/85	06/26/85		
-112	NCPLX	ASMD LKR	IS/IP	33	3	0	0.0	0.0	3	0	30	0	F	F	05/ 31/8 5	05/29/85		
-201	NCPLX	ASMD LKR	IS/IP	29	1	3	0.0	0.0	4	0	28	0	M	M	04/28/82	11/12/86	06/22/05	
-202	NCPLX	SOUND	IS/IP	27	o	3	0.0	0.0	3	o	27	0	P	M	05/31/85	05/29/85		
-203	NCPLX	ASMD LKR	IS/IP	51	1	5	0.0	0.0	6	0	50	o	PM	PM	05/31/84	11/13/86	20112132	
-204	NCPLX	ASMD LKR	IS/IP	50	1	5	0.0	0.0	6	0	49	0	P	M	05/31/84	10/22/87		
6 SIN	GLE-SHELL	TANKS	TOTALS	2057	15	164	0.0	0.0	179	80	1697	345						
						107	<u> </u>		175	- O	109/	345	L		I			ł

Ţ

TABLE E-5. INVENTORY AND STATUS BY TANK - DOUBLE SHELL TANKS

April 30, 1997

		TANK S	STATUS					LIQU	ND VOLUM	/E	Se	OLIDS VOL	UME	VOLU	ME DETERN	INATION	PHOTOS	/VIDEOS	
				EQUIVA- LENT	TOTAL	AVAIL.	SUPER- NATANT	DRAIN- ABLE INTER-	DRAIN- ABLE LIQUID	PUMP- ABLE LIQUID				LIQUID	SOLIDS	SOLIDS	LAST	LAST	SEE FOOTNO FOR
	WAST	TANK	TANK	WASTE	WASTE	SPACE	FIGUID	STIT.	REMAIN	REMAIN	DSS	SLUDGE	SALT	VOLUM	VOLUME	VOLUME	IN-TANK	IN-TANK	THESE
TANK	MATL	INTEGRITY	USE	INCHES		(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)	(Kgal)			!	METHOD	UPDATE	РНОТО	VIDEO	CHANGE
				•					A B. (T. A B.)	7 F 4 D 3 4 4	ante a rice co								
AN-101	DN	SOUND	DRCVR	42.5	117	1023	l 84	0	AN TANI 84		1			1	c	oa inoine	مرمرم		ı
AN-101		SOUND	CWHT	390.9	1075	65	986	-		84	0	33	0	FM	S	04/30/96	0/0/0		
AN-102		SOUND	CWHT	347.3	955	185	545	3	989 E4E	986	·	89	0	FM	s	08/22/89	0/0/0		(1)
AN-104		SOUND	CWHT	383.6	1055	85	606	48	545 654	545 632	410	0 449	0	FM FM	s s	03/31/97 03/31/97	10/29/87 08/19/88		(1)
AN-105		SOUND	CWHT	409.8	1127	13	638	53	691	669	ľő	449	0	FM	S				(1)
AN-106		SOUND	CWHT	79.6	219	921	202	0	202	202	0	17	0	FM	5 S	03/31/97 08/22/89	01/26/88		
AN-107		SOUND	CWHT	383.6	1055	85	808	23	831	809	0	247	0	FM	S	08/22/89	09/01/88		
						00		13	031	003	ľ	247	J	'"	3	00/22/05	03/01/60		ł
7 DOUB	LE-SHEL	TANKS		TOTALS	5603	2377	3869	127	3996	3927	410	1324	0						
AP-101	DSSF	SOUND	DRCVR	405.5	4445	25	1		AP TANI				_	1	_		l		
AP-102		SOUND	GRTFD	398.2	1115 1095	25 45	1115	0	1115	1115	0	0	0	FM	S	05/01/89	0/ 0/ 0		1
AP-103		SOUND	DRCVR	396.2 8.4	23	1117	1095	0	1095 22	1095	0	0	0	FM	S	07/11/89	0/ 0/ 0		1
AP-104		SOUND	GRTFD	9,5	26	1114	22 26	0		22	0	;	0	FM	S	05/31/96	0/0/0		İ
AP-105		SOUND	CWHT	60.4	166	974	12	11	26 23	26 12	0	154	0	FM	s	10/13/88	0/ 0/ 0	00/07/05	
AP-106		SOUND	DRCVR	118,9	327	B13	327	0	327	327	0	154 0	0	FM FM	s s	04/30/96	0/0/0	09/27/95	` [
AP-107		SOUND	DRCVR	10.5	29	1111	29	0	29	29	0	0	0	FM		10/13/88	0/0/0		1
AP-108		SOUND	DRCVR	92.7	255	885	255	0	255	25 255	0	0	0	FM FM	S S	10/13/88 10/13/88	0/ 0/ 0 0/ 0/ 0		
			5115711		200		255		200	255	•		U	""	3	10/13/66	0/0/0		Ì
8 DOUB	LE-SHELI	TANKS		TOTALS	3036	6084	2881	11	2892	2881	0	155	0						1
								į	AW TAN	K FARM !	STATUS								
AW-101	DSSF	SOUND	CWHT	409.1	1125	15	819	30	849	827	0	306	0	l FM	s	03/31/97	03/17/88		1 (0)
AW-102	DN	SOUND	EVFD	33.1	91	1049	55	0	55	55	ŏ	36	0	FM	s	04/30/96	02/02/83		[`''
AW-103	DN/PD	SOUND	DRCVR	186.2	512	628	149	37	186	164	0	363	0	FM	s	02/01/89	0/ 0/ 0		
AW-104	DN	SOUND	DRCVR	406.9	1119	21	829	49	878	856	0	179	111	FM	s	03/05/87	02/02/83		
AW-105	DN/PD	SOUND	DRCVR	159.3	438	702	158	27	185	163	0	280	0	FM	s	05/31/96	0/ 0/ 0		
AW-106	DSSF	SOUND	SRCVR	330.5	909	231	684	20	704	684	o	225	0	FM	s	04/30/96			
S DOLLE	LE-SHELL	TANKS		TOTALS	4194	2040	2004	400	0057			1.000		ļ					ļ
~ DOOD	TE. OHIEFT	LAMING		TOTALS	4134	2646	2694	163	2857	2749	0	1389	111	I					1

TABLE E-3. PUMPING RECORD, LIQUID STATUS AND PUMPABLE LIQUID REMAINING IN TANK FARMS

April 30, 1997

			Waste Vo	olumes (Kgallons)				
TANK F <u>ARMS</u> EAST	PUMPED I	PUMPED FY TO DATE	CUMULATIVE TOTAL PUMPED 1979 TO DATE	SUPERNATANT LIQUID	DRAINABLE INTERSTITIAL REMAINING	DRAINABLE LIQUID REMAINING	PUMPABLE LIQUID <u>REMAINING</u>	
Α	0.0	0.0	150.5	9	441	450	441	
ΑN	N/A	N/A	N/A	3869	127	3996	N/A	
AP	N/A	N/A	N/A	2881	11	2892	N/A	
AW	N/A	N/A	N/A	2694	163	2857	N/A	
AX	0.0	0.0	13.0	3	370	373	344	
AY	N/A	N/A	N/A	1612	4	1616	N/A	
AZ	N/A	N/A	N/A	1681	4	1685	N/A	
3	0.0	0.0	0.00	15	164	179	80	
BX BY	N/A	0.0	200.2	21	107	129	N/A	
	3.1	0.0	1570.8	0	516	516	397	
C	0.0	0.0	103.0	172	174	346	272	
Total	3.1	0.0	2037.5	12957	2081	15039	1534	9881247 113145
WEST								
S	0.0	0.0	853.6	58	1173	1231	1138	
SX	0.0	0.0	113.2	63	1298	1361	1445	
SY	N/A	N/A	N/A	2013	0	2013	N/A	
Τ	3.1	4.5	139.6	31	185	216	173	
ΓX	N/A	0.0	1205.7	5	250	255	N/A	
ΓY	N/A	0.0	29.9	3	31	34	N/A	
J	0.0	0.0	0.0	168	1138	1306	1377	
Total	3.1	4.5	2342.0	2341	4075	6416	4133	dyerde. Algeger

⁽¹⁾ Volume based on 21% (sludge waste) and 50% (saltcake waste) liquid in solid (porosity) value, per WHC-SD-W236A-ES-012, Rev .1, dated May 21, 1996, a re-evaluation of the non-stabilized tanks.

N/A = Not applicable for Double-Shell Tank Farms, and Single-Shell Tank Farms which have been declared Controlled, Clean and Stable (BX, TX, TY).

TABLE E-1. MONTHLY SUMMARY TANK STATUS

April 30, 1997

	200	200	
•	EAST AREA	WEST AREA	<u>TOTAL</u>
IN SERVICE	25	03	28 (1)
OUT OF SERVICE	66	83	149
SOUND	59	51	110
ASSUMED LEAKER	32	35	67
INTERIM STABILIZED	58	59	117. (2)
ISOLATED			
PARTIAL INTERIM	11	30	41
INTRUSION PREVENTION COMPLETE	55	53	108
CONTROLLED, CLEAN, AND STABLE	12	24	36

WASTE VOLUMES (Kgallons)							
		200	200		SST	DST	
		EAST AREA	WEST AREA	<u>TOTAL</u>	TANKS	<u>TANKS</u>	TOTAL
SUPERN	<u>ATANT</u>						
AGING	Aging waste	1681	0	1681	0	1681	1681
CC	Complexant concentrate waste	1999	1451	3450	3	3447	3450
CP	Concentrated phosphate waste	1095	0	1095	´ o	1095	1095
DC	Dilute complexed waste	1065	1	1066	2	1064	1066
DN	Dilute non-complexed waste	2187	0	2187	0	2187	2187
DN/PD	Dilute non-complex/PUREX TRU solid	307	0	307	0	307	307
DN/PT	Dilute non-complex/PFP TRU solids	0	562	562	0	562	562
NCPLX	Non-complexed waste	207	279	486	486	0	486
DSSF	Double-shell slurry feed	4416	48	4464	57	4407	4464
TOTAL	L SUPERNATANT	12957	2341	15298	548	14750	15298
<u>SOLIDS</u>					44 7544 4 7 4 4		
Doubl	e-shell slurry	410	0	410	0	410	410
Sludg	e	9382	6248	15630	12034	3596	15630
Saltca	ake	6280	16809	23089	22974	115	23089
TOTA	L SOLIDS	16072	23057	39129	35008	4121	39129
TO	TAL WASTE	29029	25398	54427	35556	18871	54427
AVAILĀI	BLE SPACE IN TANKS	11480	929	12409	0	12409	12409
DRAINA	BLE INTERSTITIAL	2081	4075	6156	5847	309	6156
DRAINAI	BLE LIQUID REMAINING	15039	6416	21455	6396	15059	21455

⁽¹⁾ Includes six double-shell tanks on Hydrogen Watch List not currently allowed to receive waste, AN-103, AN-104, AN-105, AW-101, SY-101, and SY-103.


⁽²⁾ Includes one tank (B-202) which does not meet current established supernatant and interstitial liquid stabilization criteria.

This page intentionally left blank

Liquid Observation Well

Surface Level Probe

FIGURE D-3. SINGLE-SHELL TANK INSTRUMENTATION CONFIGURATION



HNF-EP-0182

FIGURE D-1. HIGH-LEVEL WASTE TANK CONFIGURATION

HNF-EP-0182-109

COLUMN HEADING	VOLUME CALCULATIONS/DEFINITIONS
Pumped This Month	Net total gallons of liquid pumped from the tank during the month. If supernate is present, pump production is first subtracted from the supernatant volume. The remainder is then subtracted from the drainable interstitial liquid volume. The total pumped volume is subtracted from drainable liquid remaining and pumpable liquid remaining. Pump production takes into account the amount of water added to the tank during the month (if any).
Total Pumped	Cumulative net total gallons of liquid pump from 1979 to date.
Drainable Liquid Remaining	Supernate plus Drainable Interstitial. (See Supernatant Liquid and Drainable Interstitial Liquid above for definitions). The total Drainable Liquid Remaining is the sum of drainable interstitial liquid and supernate minus total gallons pumped.
Pumpable Liquid Remaining	Drainable Liquid Remaining minus undrainable heel volume. (Dish bottom tanks have a "heel" where liquids can collect: flat bottom tanks do not). (See Drainable Liquid Remaining and Pumped this Month for definitions). Not all drainable interstitial liquid is pumpable. It is assumed that drainable interstitial liquid on top of the undrainable heel in sludge or saltcake, is not jet pumpable. Therefore, pumpable interstitial liquid is the initial volume of drainable interstitial liquid minus the amount of interstitial liquid on top of the heel. The volume shown as Pumpable Liquid Remaining is the sum of pumpable interstitial liquid and supernate minus total gallons pumped.
Sludge	Solids formed during sodium hydroxide additions to waste. Sludge usually was in the form of suspended solids when the waste was originally received in the tank from the waste generator. In-tank photographs or videos may be used to estimate the volume.
Saltcake	Results from crystallization and precipitation after concentration of liquid waste, usually in an evaporator. If saltcake is layered over sludge, it is only possible to measure total solids volume. In-tank photographs or videos may be used to estimate the saltcake volume.
Solids Volume Update	Indicates the latest update of any change in the solids volume.
Solids Update Source - See Footnote	Indicates the source or basis of the latest solids volume update.
Last In-tank Photo	Date of last in-tank photographs taken.
Last In-tank Video	Date of last in-tank video taken.
See Footnotes for These Changes	Indicates any change made the previous month. A footnote explanation for the change follows the Inventory and Status by Tank section (Table E-6).

ENRAF 854 ATG Level Detector

FICs and some manual tapes are in the process of being replaced by the ENRAF ATG 854 level detector. The ENRAF gauge, fabricated by ENRAF Incorporated, determines waste level by detecting variations in the weight of a displacer suspended in the tank waste. The displacer is connected to a wire wound onto a precision measuring drum. A level causes a change in the weight of the displacer which will be detected by the force transducer. Electronics within the gauge causes the servo motor to adjust the position of the displacer and compute the tank level based on the new position of the displacer drum. The gauge displays the level in decimal inches. The first few ENRAFs that received remote reading capability transmit liquid level data via analog output to the Tank Monitor and Control System (TMACS). The remaining ENRAFs and future installations will transmit digital level data to TMACS via an ENRAF Computer Interface Unit (CIU). The CIU allows fully remote communication with the gauge, minimizing tank farm entry.

Annulus

The annulus is the space between the inner and outer shells on DSTs only. Drain channels in the insulating and/or supporting concrete carry any leakage to the annulus space where conductivity probes are installed. Alarms from the annunciators are received by CASS. Continuous Air Monitoring (CAM) alarms are also located in the annulus. The annulus conductivity probes and radiation detectors are the primary means of leak detection for all DSTs.

Liquid Observation Well (LOW)

In-tank liquid observation wells are used for monitoring the interstitial liquid level (ILL) in single-shell waste storage tanks. The wells are usually constructed of fiberglass or TEFZEL-reinforced epoxy-polyester resin (TEFZEL, a trademark of E. I. du Pont de Nemours & Company). There are a few LOWs constructed of steel. LOWs are sized to extend to within 1 inch of the bottom of the waste tank, are sealed at their bottom ends and have a nominal outside diameter of 3.5 inches. Two probes are used to monitor changes in the ILL; gamma and neutron, which can indicate intrusions or leakage by increases or decreases in the ILL. There are 65 LOWs (64 are in operation) installed in SSTs that contain or are capable of containing greater than 50 Kgallons of drainable interstitial liquid, and in two DSTs only. The LOWs installed in two DSTs, (SY-102 and AW-103 tanks), are used for special, rather than routine, surveillance purposes only.

Thermocouple (TC)

A thermocouple is a thermoclectric device used to measure temperature. More than one thermocouple on a device (probe) is called a thermocouple tree. In DSTs there may be one or more thermocouple trees in risers in the primary tank. In addition, in DSTs only, there are thermocouple elements installed in the insulating concrete, the lower primary tank knuckle, the secondary tank concrete foundation, and in the outer structural concrete.

These monitor temperature gradients within the concrete walls, bottom of the tank, and the domes. In SSTs, one or more thermocouples may be installed directly in a tank, although some SSTs do not have any trees installed. A single thermocouple (probe) may be installed in a riser, or lowered down an existing riser or LOW. There are also four thermocouple laterals beneath Tank 105-A in which temperature readings are taken in 34 thermocouples.

In-tank Photographs and Videos

In-tank photographs and videos may be taken to aid in resolving in-tank measurement anomalies and determine tank integrity. Photographs and videos help determine sludge and liquid levels by visual examination.

TERMS/ACRONYMS

CASS Computer Automated Surveillance System

<u>CCS</u> Controlled, Clean and Stable (tank farms)

II Interim Isolated

INTERIM STABILIZATION (Single-Shell Tanks only)

Interim Stabilized (IS)

A tank which contains less than 50 Kgallons of drainable interstitial liquid and less than 5 Kgallons of supernatant liquid. If the tank was jet pumped to achieve interim stabilization, then the jet pump flow must also have been at or below 0.05 gpm before interim stabilization criteria is met.

Jet Pump

The jet pump system includes 1) a jet assembly with foot valve mounted to the base of two pipes that extend from the top of the well to near the bottom of the well casing inside the saltwell screen, 2) a centrifugal pump to supply power fluid to the down-hole jet assembly, 3) flexible or rigid transfer jumpers, 4) a flush line, and 5) a flowmeter. The jumpers contain piping, valves, and pressure and limit switches.

The centrifugal pump and jet assembly are needed to pump the interstitial liquid from the saltwell screen into the pump pit, nominally a 40-foot elevation rise. The power fluid passes through a nozzle in the jet assembly and acts to convert fluid pressure head to velocity head, thereby reducing the pressure in the jet assembly chamber. The reduction in pressure allows the interstitial liquid to enter the jet assembly chamber and mix with the power fluid. Velocity head is converted to pressure head above the nozzle, lifting power fluid, and interstitial liquid to the pump pit. Pumping rates vary from 0.05 gallons to about 4 gpm.

Saltwell Screen

The saltwell system is a 10-inch diameter saltwell casing consisting of a stainless steel saltwell screen welded to a Schedule 40 carbon steel pipe. The casing and screen are to be inserted into the 12-inch tank riser located in the pump pit. The stainless steel screen portion of the system will extend through the tank waste to near the bottom of the tank. The saltwell screen portion of the casing is an approximately 10-foot length of 300 Series, 10-inch diameter, stainless steel pipe with screen openings (slots) of 0.05 inches.

Emergency Pumping Trailer

A 45-foot tractor-type trailer is equipped to provide storage space and service facilities for emergency pumping equipment: this consists of two dedicated jet pump jumpers and two jet pumps, piping and dip tubes for each, two submersible pumps and attached piping, and a skid-mounted Weight Factor Instrument Enclosure (WFIE) with an air compressor and electronic recording instruments. The skid also contains a power control station for the pumps, pump pit leak detection, and instrumentation. A rack for over 100 feet of overground double-contained piping is also in the trailer.

INTRUSION PREVENTION (ISOLATION) Single-Shell Tanks only

Partially Interim Isolated (PI)

The administrative designation reflecting the completion of the physical effort required for Interim Isolation except for isolation of risers and piping that is required for jet pumping or for other methods of stabilization.

Interim Isolated (II)

The administrative designation reflecting the completion of the physical effort required to minimize the addition of liquids into an inactive storage tank, process vault, sump, catch tank, or diversion box. In June 1993, Interim Isolation was replaced by Intrusion Prevention.

Intrusion Prevention (IP)

Intrusion Prevention is the administrative designation reflecting the completion of the physical effort required to minimize the addition of liquids into an inactive storage tank, process vault, sump, catch tank, or diversion box. Under no circumstances are electrical or instrumentation devices disconnected or disabled during the intrusion prevention process (with the exception of the electrical pump)

Controlled, Clean, and Stable (CCS)

Controlled, Clean, and Stable reflects the completion of several objectives: "Controlled" - provide remote monitoring for required instrumentation and implement controls required in the TWRS Authorization Basis; "Clean" - remove surface soil contamination and downpost the Tank Farms to RBA/URMA/RA radiological

C. TANK AND EQUIPMENT CODE/STATUS DEFINITIONS

April 30, 1997

1. TANK STATUS CODES

WASTE TYPE (also see definitions, section 3)

AGING Aging Waste (Neutralized Current Acid Waste [NCAW])

CC Complexant Concentrate Waste
CP Concentrated Phosphate Waste
DC Dilute Complexed Waste
DN Dilute Non-Complexed Waste

DSS Double-Shell Slurry
DSSF Double-Shell Slurry Feed
NCPLX Non-Complexed Waste

PD/PN Plutonium-Uranium Extraction (PUREX) Neutralized Cladding

Removal Waste (NCRW), transuranic waste (TRU)

PT Plutonium Finishing Plant (PFP) TRU Solids

TANK USE (DOUBLE-SHELL TANKS ONLY)

CWHT Concentrated Waste Holding Tank

DRCVR Dilute Receiver Tank
EVFD Evaporate Feed Tank
SRCVR Slurry Receiver Tank

2. SOLID AND LIQUID VOLUME DETERMINATION METHODS

- F Food Instrument Company (FIC) Automatic Surface Level Gauge
- E ENRAF Surface Level Gauge (being installed to replace FICs)
- M Manual Tape Surface Level Gauge
- P Photo Evaluation
- S Sludge Level Measurement Device

3. **DEFINITIONS**

WASTE TANKS - GENERAL

Waste Tank Safety Issue

A potentially unsafe condition in the handling of waste material in underground storage tanks that requires corrective action to reduce or eliminate the unsafe condition.

Watch List Tank

An underground storage tank containing waste that requires special safety precautions because it may have a serious potential for release of high level radioactive waste because of uncontrolled increases in temperature or pressure. Special restrictions have been placed on these tanks by "Safety Measures for Waste Tanks at Hanford Nuclear Reservation," Section 3137 of the *National Defense Authorization Act for Fiscal Year 1991*, November 5, 1990, Public Law 101-510, (also known as the Wyden Amendment).

Characterization

Characterization is understanding the Hanford tank waste chemical, physical, and radiological properties to the extent necessary to insure safe storage and interim operation, and ultimate disposition of the waste.

This page intentionally left blank

Table B-2. Double Shell Tank Waste Inventory for April 30, 1997

	CE AS OF	APRIL 30, 1997:	12409	KGAL
WATCH LIST TANK SPACE:	TANK	WASTE TYPE	AVAILABLE	SPACE
Inusable DST Headspace - Due to Special Restrictions	101-AW	DSSF	15	KGALS
laced on the Tanks, as Stated in the "Wyden Bill"	101-SY	CC	26	KGALS
	103-SY	CC	396	KGALS
	103-AN	DSS	185	KGALS
	104-AN	DSSF	85	KGALS
	105-AN	DSSF	13	KGALS
		TOTAL	_= 720	KGAL
	,	AVAILABLE TANK SPACE=	12409	KGALS
	MI	NUS WATCH LIST SPACE=	-720	KGALS
TOTAL AVAILABLE SPACE AFT	ER WATCH L	IST SPACE DEDUCTIONS=	11689	KGAL
EGREGATED TANK SPACE:	TANK	WASTE TYPE	AVAILABLE	SPACE
ST Headspace Available to Store Only Specific Waste Type	102-AP	CP	45	KGALS
	108-AP	DC	885	KGALS
	101-AY	DC	77	KGALS
	102-AN	CC	65	KGALS
	106-AN	cc	921	KGALS
	107-AN	CC	85	KGALS
	101-AZ	AW	73	KGALS
	102-AZ	AW	76	KGALS
		TOTAL	= 2227	KGALS
AVAILABLE SP/	ACE AFTER \	WATCH LIST DEDUCTIONS	= 11689	KGALS
		US SEGREGATED SPACE=		KGALS
TOTAL AVAILABLE SPACE AFTE	R SEGREGA	TED SPACE DEDUCTIONS:		KGALS
ISABLE/WASTE RECEIVER TANK SPACE:	TANK	WASTE TYPE	AVAILABLE	SPACE
ST Headspace Available to Store Facility Generated	101-AP	DSSF		KGALS
nd Evaporator Product Waste	103-AP	DN	1117	KGALS
	104-AP	DN	1114	KGALS
	105-AP	DN	974	KGALS
FACILITY WASTE RECEIVER TANK	106-AP	DN		KGALS
TACILITY WAS TE RECEIVER TAIN	407.40			KONLO
TAGISTI WASTE RECEIVER TANK	107-AP	DN	1111	NOALS
EVAPORATOR FEED TANK	107-AP 102-AW	DN DN		
			1049	KGALS
	102-AW	DN	10 4 9 628	KGALS KGALS
	102-AW 103-AW	DN NCRW	1049 628 21	KGALS KGALS KGALS
	102-AW 103-AW 104-AW	DN NCRW DN	1049 628 21 702	KGALS KGALS KGALS KGALS
EVAPORATOR FEED TANK	102-AW 103-AW 104-AW 105-AW	DN NCRW DN NCRW	1049 628 21 702 231	KGALS KGALS KGALS KGALS KGALS
EVAPORATOR FEED TANK EVAPORATOR RECEIVER TANK	102-AW 103-AW 104-AW 105-AW 106-AW	DN NCRW DN NCRW DSSF	1049 628 21 702 231 1023	KGALS KGALS KGALS KGALS
EVAPORATOR FEED TANK EVAPORATOR RECEIVER TANK	102-AW 103-AW 104-AW 105-AW 106-AW 101-AN	DN NCRW DN NCRW DSSF DN	1049 628 21 702 231 1023 147	KGALS KGALS KGALS KGALS KGALS KGALS
EVAPORATOR FEED TANK EVAPORATOR RECEIVER TANK FACILITY WASTE RECEIVER TANK FACILITY WASTE RECEIVER TANK	102-AW 103-AW 104-AW 105-AW 106-AW 101-AN 102-AY 102-SY	DN NCRW DN NCRW DSSF DN DN	1049 628 21 702 231 1023 147 507	KGALS KGALS KGALS KGALS KGALS KGALS KGALS
EVAPORATOR FEED TANK EVAPORATOR RECEIVER TANK FACILITY WASTE RECEIVER TANK FACILITY WASTE RECEIVER TANK	102-AW 103-AW 104-AW 105-AW 106-AW 101-AN 102-AY 102-SY AL AVAILABI	DN NCRW DN NCRW DSSF DN DN	1049 628 21 702 231 1023 147 507	KGALS KGALS KGALS KGALS KGALS
EVAPORATOR FEED TANK EVAPORATOR RECEIVER TANK FACILITY WASTE RECEIVER TANK FACILITY WASTE RECEIVER TANK TOTA	102-AW 103-AW 104-AW 105-AW 106-AW 101-AN 102-AY 102-SY AL AVAILABI	DN NCRW DN NCRW DSSF DN DN	1049 628 21 702 231 1023 147 507 9462	KGALS KGALS KGALS KGALS KGALS KGALS KGALS

TABLE B-1. DOUBLE-SHELL TANK WASTE TYPE AND SPACE ALLOCATION APRIL 1997

DOUBLE-SHELL TANK INVENTOR	RY BY WASTE TY	PE SPACE DESIGNATED FOR SPECIFIC	USE	
Complexed Waste	4.52 Mgal	Spare Tanks (3)	2.28	Mgal
(102-AN, 106-AN, 107-AN, 101-SY,		(1 Aging & 1 Non-Aging Waste Tank)		
103-SY, (101-AY , 108-AP (DC))				
		Watch List Tank Space	0.72	Mgal
Concentrated Phosphate Waste	1.1 Mgal	(103-AN, 104-AN, 105-AN, 101-SY, 103-SY, 101	1-AW)	
(102-AP)	1			
Double-Shell Slurry and Slurry Feed	4.49 Mgal	Segregated Tank Space	2.23	Mgal
(103-AN, 104-AN, 105-AN, 101-AP,		(102-AN, 106-AN, 107-AN, 102-AP, 108-AP, 10	1-AY	
101-AW, 106-AW)		101-AZ, 102-AZ)		
Aging Waste (NCAW) at 5M Na	1.23 Mgal	Receiver/Operational Tank Space (2)	3.48	Mgal
Dilute in Aging Tanks	0.45 Mgal	(101-AN, 106-AP, 102-SY, 102-AW, 106-AW)		_
(101-AZ, 102-AZ)	-			
Dilute Waste (1)	3.02 Mgal			
(101-AN, 103-AP, 105-AP, 106-AP, 107-AP, 102-AW, 103-AW, 104-AW, 105-AW, 102-AY, 102-SY, 104-AP)		Total Specific Use Space (04/30/97)	8.71	Mgal
' . ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '		TOTAL DOUBLE-SHELL TANK SPACE	E	
NCRW, PFP and DST Settled Solids	4.06 Mgal	24 Tanks at 1140 Kgal	27.36	Mgal
(All DSTs)		4 Tanks at 980 Kgal	3.92	Mgal
			31.28	Mgal
Total Inventory=	18.87 Mgal	Total Available Space	31.28	Mgal
		Double-Shell Tank Inventory	18.87	Mgal
		Space Designated for Specific Use	8.71	Mgal
		Remaining Unallocated Space	3.70	Mgal

⁽¹⁾ Was reduced in volume by -0.02 Mgal this month (Evaporator WVR)

Note: Net change in total DST inventory since last month: +0.057 Mgal

WVPTOT

⁽²⁾ Tank Space Reduced by Facility Generations and Saltwell Liquid pumping

^{(3) 241-101-}AY: A minumum liquid level is set to provide extra protection against any bottom uplifting of the tank's steel liner. Because of space availability, waste is stored in 102-AY, the aging waste spare tank. In case of a leak the contents of 102-AY will be distributed to any other DST(s) having available space.

HNF-EP-0182-109

TABLE A-8. TANK MONITOR AND CONTROL SYSTEM (TMACS) April 30, 1997

Note: Acceptance Testing has been completed on the following sensors

Sensors Automatically Monitored by TMACS

	Temperatures					· · · · · · · · · · · · · · · · · · ·
		Resistance				
EAST AREA	Thermocouple	Thermal	ENRAF			Gas
	Tree	Device	Level			Sample
Tank Farm	(TC)	(RTD)	Gauge	Pressure	Hydrogen	Flow
A-Farm (6 Tenks)	(,	(1110)		11033010	Hydrogen	11044
AN-Farm (7 Tanks)	10 (d)		4	7	- 	
AP-Farm (8 Tanks)			-		· · · · · · · · · · · · · · · · · · ·	
AW-Farm (6 Tanks)						
AX-Farm (4 Tanks)	1					·
AY-Farm (2 Tanks)						
AZ-Farm (2 Tanks)			· · · · · · · · · · · · · · · · · · ·			
B-Farm (16 Tanks)		· · · · · · · · · · · · · · · · · · ·				
BX-Farm (12 Tanks)	11		12		-	
BY-Farm (12 Tanks)	10	3				
C-Farm (16 Tanks)	15	1	3	1		···
TOTAL EAST AREA						
(91 Tanks)	43 .	4	15	8	0	0
WEST AREA						
S-Farm (12 Tanks)	12		4	1	3	3
SX-Farm (15 Tanks)	14		1	1	7	7
SY-Farm (3 Tanks)	3		1	1	2	1
T-Farm (16 Tanks)	14	11	3			-
TX-Farm (18 Tanks)	14		18			
TY-Farm (6 Tanks)	6	3	6			
U-Farm (16 Tanks)	15		5	4	5	5
TOTAL WEST AREA						<u> </u>
(86 Tanks)	82	4	37	7	17	16
TOTALS (177 Tanks)	124	8	57	15(b)	17(c)	19(a)

⁽a) Tank SY-101 has 2 gas sample flow sensors plus 2 vent flow sensors, and 2 ENRAFs.

⁽b) Each tank has low and high range sensors (9x2=18 sensors)

⁽c) Each tank has low and high range sensors (17x2=34 sensors)

⁽d) 3 tanks in AN farm have 2 TC trees

TABLE A-6. DOUBLE-SHELL TANKS MONITORING COMPLIANCE STATUS - 28 TANKS (Sheet 2 of 2)

Footnotes:

- 1. All DSTs have both FIC and manual tape which is used when the FIC is out of service. N/C will be shown when no readings are obtained. ENRAF gauges are being installed to replace FICs. The ENRAF gauges are being connected to TMACS, but some are currently being read manually.
- 2. Psychrometric readings are taken on an "as needed" basis. Currently, monthly readings are being taken on the SY-101, SY-102, and SY-103 tank exhaust. No other psychrometric readings are currently being taken.
- 3. OSD specifies DST temperature limits, gradients, etc.
- 4. Applicable OSD and HNF-IP-0842, latest revisions, are used as guidelines for monitoring Leak Detection Pits. See also (8) below.
- 5. AY-101/102 and AZ-101/102 annulus are now monitored by an Annulus Leak Detection Probe Measurement rather than the annulus CAM.
- 6. AW-102 has ENRAF, FIC and M.T. At some point the FIC will be removed.
- 7. SY-101 and SY-103 had intermittent RAD readings due to power problems.
- 8. USQ TF-97-0038, dated April 28, 1997, specifies discontinuing the use of leak detection pit radiation monitoring equipment in all double-shell tank farms where the leak detection pits are used as tertiary leak detection. This applies to all double-shell tank farms with the exception of SY-Farm.

TABLE A-5. SINGLE-SHELL TANKS MONITORING COMPLIANCE STATUS - 149 TANKS (Sheet 6 of 6)

Tanks which will not receive LOWs:

4 103	DI 101	0.001	mtoc
A-102	BX-101	C-201	T-106
A-104	BX-103	C-202	T-108
A-105	BX-105	C-204	T-109
AX-102	BX-106	SX-110	TX-107
AX-104	BX-108	SX-113	TY-102
B-102	C-108	SX-115	TY-104
B-103	C-109	T-102	TY-106
B-112	C-111	T-103	U-101
			11-112

Total - 33 Tanks

- 9. TX-105 the riser has been removed; it has not been monitored since January 1987. Liquid levels are being taken.
- 10. All drywell scans are done by request only, when required in addition to, or as a BACKUP for, a PRIMARY leak detection method, per OSD-T-151-00031. Currently, there are only two tanks which require drywell scans (C-105 and C-106); these are taken monthly.

Only two tank farms, A and SX, have laterals. There are currently no functioning laterals and no plans to prepare these for use.

11. AX-101 - LOW reading taken by gamma rather than neutron sensor.

TABLE A-5. SINGLE-SHELL TANKS MONITORING COMPLIANCE STATUS 149 TANKS (Sheet 4 of 6)

	1		_	Primary				LOW
T 1.	Tank Ca		Temperature	Leak	Surface Level Readings (1)			Readings
Tank Number	Watch List	High Heat	Readings	Detection		(OSR,OSD)		(OSD)(6,8)
U-107	<u> </u>	neat	(5)	Source (6)	MT	FIC	ENRAF	Neutron
U-108	X			ENRAF	None	None		
U-109	X			LOW	None	None		
U-110	^			ENRAF	None	None		
U-111	Х.			None	Nore	None		None
U-112	· · · · · · · · · · · · · · · · · · ·			LOW	None	None		
U-201				None		None	None	None
U-202				MT		None	None	None
U-203	×			MT		None	None	None
U-204	X			None		None	None	None
:		<u> </u>	:!!::	MT		None	None .	None
Catch Tanks a				***************************************	Or addenosación reconación con con	Inia Bhilineacan canananan ann an		
A-302-A	N/A	N/A	N/A	(7)	None	None		None
A-302-B ER-311	N/A	NA	N/A	(7)		None	None	None
AX-152	N/A	N/A	N/A	(7)	None		None	None
AZ-152	N/A	N/A	N/A	(7)		None	None	None
AZ-161 AZ-164	N/A	N/A	NIA	(7)	None		None	None
BX-TK/SMP	N/A	NIA	NA	(7)		None	None	None
A-244 TK/SMP	N/A	NJA	NIA	17)		None	Pione	None
AR-204	N/A N/A	N/A N/A	N/A	(7)	None	None	None	None
A-417	N/A	N/A	N/A N/A	17)			None	None
A-350	N/A	N/A	anni annoningonorouccoccoccoccocc	(2)	None	None	None	None
CR-003	NIA	N/A N/A	N/A	(7)	None	None	None	None
Vent Sta.	N/A	N/A	N/A	(7)	None	None	None	None
S-302	N/A	N/A	N/A	17)		None	None	None
S-302-A	NA	N/A	N/A N/A	(2).	None	None		None
5-304	NIA	N/A	N/A	(7)	None		None	None
TX-302-B	NIA	N/A	N/A	(7)	None		None	None
TX-302-B	N/A	NIA		(7)		None	None	None
U-301-B	N/A	NIA	N/A N/A	(7)	None	None		OfS
UX-301-6	N/A	N/A	N/A	(7)	None	None		O/S
S-141	N/A	N/A	N/A	(7)	None	None		0/8
S-142	N/A	N/A	N/A	(7)		None	None	None
Totals:	32	10	N/C: 0	(7)	N/O O	None	None	None
iutais;	34	10	N/C: U		N/C: 0	N/C: 0	N/C: 0	N/C: 8
149 tanks	Watch	High					1	
TO COUNT	List	Heat						1
	Tanks	Tanks			ļ	1		
	(4)	(4)	1			1	1	

TABLE A-5. SINGLE-SHELL TANKS MONITORING COMPLIANCE STATUS 149 TANKS (Sheet 2 of 6)

Tank Category		Tank Category Temperature Leak	•	Surfac	LOW Readings			
Tank Number	Watch List	High Heat	Readings	Detection Source (6)	MT (0	OSR,OSD)	LEUDAE	(OSD)(6,8)
8X-108	LISC	Певс	(5)		<u> </u>		ENRAF	Neutron
BX-108		66 88 (5868) 888 (888)		None None	O/S None	None None		None
BX-109	_			None	0/5	None		None None
BX-111	2 52 53 53 53			LOW	0/5	None		MONE
BX-112		+		ENRAF	None	None		None
BY-101		1		LOW		None	None	13.71.5
BY-102			None	row		None	None	
BY-103				LOW ,		None	None	
BY-104				LOW		None	None	
BY-105				LOW		None	None	
BY-106				LOW		None	None	
BY-107				LOW		None	None	
BY-108				None		None	None	None
BY-109			None	LOW	None		None	
BY-110				LOW		None	None	
BY-111				LOW		None	None	
BY-112				LOW		None	None	
C-101				None		None	None	None
C-102	×			None	None		None	None
C-103	Ж			ENRAF	None	None		None
C-104				None	None		None	None
C-105				None	None	None		None
C-106 (4)	×	×		ENRAF	None	0/\$		None
C-107				ENRAF	None	None		None
C-108				None .		None	None	None
C-109				None		None	None	None
C-110				MT		None	None	None
C-111				None		None	Norte	None
C-112				None	None	None		None
C-201				None		None	None	None
C-202				None		None	None	None
C-203				None		None	None	None
C-204			None	None		None	None	None
S-101				ENRAF	None	None		
S-102	ж			ENRAF	None	None		
S-103				ENRAF	None	None		
S-104				LOW		None	None	
S-105				LOW	None	None		
S-106				ENRAF	None	None		
S-107				ENRAF	None	None		None
S-108				LOW	0/5	None		
S-109				LOW	None	None		
S-110				row	None	None		
S-111	×			ENRAF	None	None		
S-112	×			LOW .	None	None		
SX-101	×			LOW	None	None		
SX-102	Х	I		LOW	None	None		
SX-103	×			LOW	None	None		
SX-104	ж			LOW	None	None		
SX-105				LOW	None	None		
SX-106	T ×			ENRAF	O/S	None		
SX-107		X		None		None	None	None
SX-108		×		None		None	None	None

HNF-EP-0182-109

TABLE A-4. TEMPERATURE MONITORING IN NON-WATCH LIST TANKS April 30, 1997

SINGLE-SHELL TANKS WITH HIGH HEAT LOADS (>40,000 Btu/hr)

Ten tanks have high heat loads for which temperature surveillance requirements are established by SD-WM-OSR-005 and OSD-T-151-00013. Only one of these tanks (241-C-106) is on the High Heat Watch List. In an analysis, WHC-SD-WM-ER-333, "Evaluation of Heat Sources in High Heat Single Shell Tanks," Bander, 1994, it was determined that six of the ten tanks have heat sources greater than 40,000 Btu/h. Additionally, although four tanks have heat loads less than 40,000 Btu/h, it is recommended that these tanks remain on the High Heat Load List due to uncertainties in the parameters used in these analyses. It is estimated that the current analysis predicts the heat loads within +/- 20%.

Temperatures in these tanks did not exceed OSR or OSD requirements for this month. All high heat load tanks, with the exception of 241-A-104 and 241-A-105, are on active ventilation. All high heat load tanks are monitored by the Tank Monitor and Control System (TMACS), with the exception of A-104 and A-105, which are taken manually on a weekly basis.

	Temperature	Total Waste
Tank No.	(F.)	In Inches
A-104	166	10
A-105	136	07
C-106 (*)	144	72
SX-107	164	43
SX-108	186	37
SX-109	145	96
SX-110	161	28
SX-111	187	51
SX-112	144	39
SX-114	179	71
10 Tanks		

(*) C-106 on High Heat Load Watch List

Highest temperature in 34 lateral thermocouples beneath A-105: 238

SINGLE SHELL TANKS WITH LOW HEAT LOADS (<=40,000 Btu/hr)

There are 108 low heat load non-watch list tanks. Temperatures in tanks connected to TMACS are monitored by TMACS; temperatures in those tanks not yet connected to TMACS are manually taken semiannually in January and July. Temperatures obtained were within historical ranges for the applicable tank.

No temperatures have been obtained for several years in the tanks listed below. Most of these tanks have no thermocouple tree.

Tank No.	<u>Tank No.</u>
BX-104	TX-101
BY-102	TX-110
BY-109	TX-114
C-204	TX-116
SX-115	TX-117
T-102	U-104
T-105	

TABLE A-3. TEMPERATURE MONITORING IN WATCH LIST TANKS (Sheet 1 of 2) April 30, 1997

All Watch List tanks are reviewed for increasing temperature trends. Temperatures in these tanks are monitored by the Tank Monitor And Control System (TMACS), unless indicated otherwise.

Temperatures are taken in the waste unless in-waste thermocouples are out of service. See footnote (3). Temperatures below are the highest temperatures recorded in these tanks during this month, and do not exceed the maximum criteria limit for this month.

Temperatures in Degrees F.
Total Waste in Inches

Hydro/Flammable Gas		Orga	Organic Salts			High Heat		
		Total			Total	1	Total	
Tank No.	Temp.	<u>Waste</u>	<u>Tank No.</u>	<u>Temp.</u>	<u>Waste</u>	Tank No.	Temp. Waste	
A-101 (*)	151	347	A-101 (*)	151	347	C-106 (2)	144 72	
AX-101 (*)(3)	132	272	AX-102 (*)	72	14	1 Tank		
AX-103 (*)	107	40	B-103 (*)(3)	58	17			
S-102	106	207	C-102	80	149			
S-111	91	224	C-103	111	66			
S-112	84	239	S-102	106	207	}		
SX-101	134	171	S-111	91	224			
SX-102	145	203	SX-103	168	242			
SX-103	167	243	\$X-106	108	201			
SX-104	162	229	T-111	62	158			
SX-105	173	254	TX-105 (*)	96	228			
SX-106	108	201	TX-118	74	134	j i		
SX-109 (1)	145	96	TY-104	60	24	İ		
T-110	63	133	U-103	86	166			
U-103	86	166	U-105	90	147			
U-105	90	147	U-106	79	78			
U-107	79	143	U-107	79	166			
U-108	88	166	U-111	79	115			
U-109	84	164	U-203	60	6			
AN-103	110	955	U-204	59	9			
AN-104	112	384	20 Tanks					
AN-105	106	410						
AW-101 (*)	100	410			•			
SY-101	118	405						
SY-103	97	270						
25 Tanks								

^(*) Temperatures in these eight tanks are taken manually on a weekly basis.

All tanks have been removed from the Ferrocyanide Watch List. See Table A-2 for list and dates.

³⁸ Tanks are on the Watch List (8 tanks are on more than one list: A-101, S-102, S-111, SX-103, SX-106, U-103, U-105, U-107)

TABLE A-1. WATCH LIST TANKS April 30, 1997

These tanks have been identified as Watch List Tanks in accordance with Public Law 101-510, Section 3137, "Safety Measures for Waste Tanks at Hanford Nuclear Reservation," (1990). These tanks have been identified as the Priority 1 Hanford Site Tank Farm Safety Issues: "Issues/situations that contain most necessary conditions that could lead to worker (onsite) or offsite radiation exposure through an uncontrolled release of fission products, e.g., SY-101."

			Officially
Added to	Double-Shell 1	anks	Added to
st Watch List	Tank No.	Watch List	Watch List
	Turk ito:	***************************************	TTACCII EISC
1/91	AN-103	11	4 10 4
		Hydrogen	1/91
5/94	AN-104	Hydrogen	1/91
1/91	AN-105	Hydrogen	1/91
5/94	AW-101	Hydrogen	6/93
1/91	SY-101	Hydrogen	1/91
1/91	SY-103	Hydrogen	1/91
5/94	6 Tanks		
1/91			
oad 1/91	TANKS BY V	VATCH LIST	
1/91			
1/91	<u>Hydrogen</u>	<u>Organics</u>	
1/91	A-101	A-101	
5/94	AX-101	AX-102	
1/91	AX-103	B-103	
1/91	S-102	C-102	
1/91	S-111	C-103	
1/91	S-112	S-102	
5/94	SX-101	S-111	
1/91	SX-102	SX-103	
1/91	SX-103	SX-106	
1/91	SX-104	T-111	
1/91	SX-105	TX-105	
ecause	SX-106	TX-118	
vent	SX-109	TY-104	
1/91	T-110	U-103	
1/91	U-103	U-105	
2/94	U-105	U-106	
1/91	U-107	U-107	
1/91	U-108	U-111	
5/94	U-109	U-203	
1/91	AN-103	U-204	
5/94	AN-104	20 Tanks	1
1/91	AN-105	(A.V. + Gilka	i
5/94	AW-101		
1/91	SY-101	High Heat	
1/91	SY-103	C-106	
12/93	25 Tanks	1 Tank	1
1/91	47 10 INA	1 I BUK	!
		. a	
		•	
5/94	38	Tanks on Watch Lists	
	1/91 8/93 5/94 5/94	8/93 32 5/94 <u>6</u>	8/93 32 Single-Shell tanks 5/94 6 Double-Shell tanks

^(*) Eight tanks are on more than one Watch List

All tanks were removed from the Ferrocyanide Watch List; see Table A-2 for list and dates.

This page intentionally left blank.

II. WASTE TANK INVESTIGATIONS

This section includes all single-shell tanks or catch tanks which are showing <u>surface level or interstitial liquid level (ILL)</u> <u>decreases</u>, or <u>drywell radiation level increases</u> in excess of established criteria.

There are currently no tanks under investigation for ILL decreases or drywell radiation level increases which exceed the criteria. Drywell monitoring is done on an "as needed basis" with the exception of C-105 and C-106 which are monitored monthly.

Catch Tank 241-AZ-154: Historical surface levels have been 0.00 inches since 1993 through January 1997. The catch tank received rain intrusion in February and the daily zipcord measurements fluxuated between 1.00 inches and 1.75 inches. At that time a baseline was established at 1.25 inches (midpoint). Since February, the levels have decreased approximately .50 inches per month until the level is now back to 0.00 inches. It was noted on the operator round sheet that the zipcord needs replacing with measured increments. Discrepancy Report #97-832 was issued on April 29, 1997.

<u>Resolution Status</u>: Cognizant engineers will submit a request to inspect and replace the zipcord if needed. Further evaluation will be required to determine if the decrease is attributed to evaporation.

A. Assumed Leakers or Assumed Re-leakers: (See Appendix C for definition of "Re-leaker")

This section includes all single- or double-shell tanks or catch tanks for which an <u>off-normal or unusual occurrence</u> report has been issued for assumed leaks or re-leaks. Tanks/catch tanks will remain on this list until either a) completion of Interim Stabilization, or b) the updated occurrence report indicates that the tank/catch tank is not an assumed leaker.

There are currently no tanks for which an off-normal or unusual occurrence report has been issued for assumed leaks or re-leaks.

B. Tanks with increases indicating possible intrusions:

This section includes all single-shell tanks and related receiver tanks for which the surveillance data show that the surface level or ILL has met or exceeded the increase criteria, or are still being investigated.

244-AR Tanks and Sumps: Currently, all ventilation systems at 244-AR are shut down. Based on the weight factor gauges for the sumps and tanks, Tank 001 contains 1300 gallons, Tank 002 contains 12,250 gallons (some unknown amount of sludge), Tank 003 contains 2000 gallons, and Tank 004 contains 250 gallons. Sump 001 contains 586 gallons, Sump 002 contains 23 gallons, and Sump 003 contains 2911 gallons. These volumes were updated April 30, 1997.

Increase criteria in the following tanks indicate possible intrusions: however, since no funds have been allocated for performing intrusion investigations in FY 1997, the details on these tanks are not included in this report. Complete information on these tanks will again appear in this report when intrusion investigation activities resume.

Tank 241-B-202 Tank 241-BX-101 Tank 241-BX-103 Tank 241-C-101

HNF-EP-0182-109

G.	MISCELLANEOUS UNDERGROUND STORAGE TANKS AND SPECIAL SURVEILLAN	ICE
	FACILITIES G-1	
	<u>Tables</u> :	
	1 Misc. Underground Storage Tanks and Special Surveillance Facilities (Active). G-2	
	2 East Area Inactive Underground Storage Tanks and Special Surveillance	
	Facilities (Inactive)	
	3 West Area Inactive Underground Storage Tanks and Special Surveillance	
	Facilities (lnactive) G-4	
н	LEAK VOLUME ESTIMATES H-1	
**.	Table:	
	1 Single-Shell Tank Leak Volume Estimates	
ī	SINGLE-SHELL TANKS INTERIM STABILIZATION, AND CONTROLLED, CLEAN	
	AND STABLE STATUS	
	Tables:	
	1 Single-Shell Tanks Interim Stabilization Status I-2	
	2 Tri-Party Agreement Single-Shell Tank Interim Stabilization	
	Schedule	
	3 Single-Shell Tanks Controlled, Clean, and Stable Status	
	4 Single-Shell Tanks Stabilization Status Summary I-6	
J.	CHARACTERIZATION PROGRESS STATUS	
J.	Figure:	
	1 Characterization Progress Status	
	1 Characterization 1 rogics Status	

METRIC CONVERSION CHART					
l inch	=	2.54 centimeters			
1 foot	=	30.48 centimeters			
l gallon	=	3.80 liters			
l ton	=	0.90 metric tons			
$^{\circ}F = \left(\frac{9}{5} ^{\circ}C\right) + 32$					
l Btu/h = 2.930711 E-01 watts (International Table)					

This page intentionally left blank.

This page intentionally left blank.

RELEASE AUTHORIZATION

Document Number:

HNF-EP-0182-109

Document Title:

Waste Tank Summary Report for Month Ending April 30,

1997

Release Date:

6/11/97

This document was reviewed following the procedures described in WHC-CM-3-4 and is:

APPROVED FOR PUBLIC RELEASE

WHC Information Release Administration Specialist:

Kara M. Broz

June 11, 1997

LEGAL DISCLAIMER.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced from the best available copy.

Printed in the United States of America

DISCLM-2.CHP (1-91)